

# Exhibit C

2004 年 8 月 31 日

大阪府枚方市牧野北町 5-3-207  
佐々木 亮一 様

松下電器産業株式会社  
R & D 知的財産権センター  
竹之内 茂雄

拝啓 時下ますますご清栄のこととお慶び申し上げます。

さて、2003 年春に佐々木様に連絡させていただいた、佐々木様が共同発明者の一人になられている米国特許第 5,767,845 号の下記再発行出願 (Reissue) に関する件で連絡させていただきます。

米国特許出願第 09/587,107 号  
発明の名称：多重媒体情報記録装置  
出願日：2000 年 6 月 2 日  
松下整理番号：P12792-02  
国内代理人整理番号：FP-95040a  
海外代理人整理番号：52478-0900 (AS70r)

本件について、米国特許庁から補正再発行出願宣誓書を提出するようにとの要請を受け取りました。この補正宣誓書は、佐々木様が 2000 年 6 月 21 日付で他の発明者の方々と一緒に署名された宣誓書を修正するためのものです。

元の宣誓書には、クレーム 26 と記載されるべきところを、クレーム 25 と記載されるという、不注意による誤りがありました。そこで、この手紙に現在のクレームを記載した最新の補充補正書と、この軽度の誤りを修正する補充再発行出願宣誓書とを同封しております。ご存知の通り、佐々木様が弊社の従業員をされていた 1998 年に米国特許第 5,767,845 号が発行されました。今回の再発行出願の目的は、この米国特許の誤りを修正することにあります。従いまして、弊社が必要としているのは、新規の特許に関するものではなく、既に存在する特許の見直しに関するものだけです。

以前、2003 年 2 月 24 日付で、手紙と上記米国特許のコピーを佐々木様に書留郵便にてお送りしました。これらの文書送付に関しては、2003 年 2 月 25 日付での配達証明を確認しております。

2003 年春、弊社より数回にわたって佐々木様に連絡を取らせていただきました。そして 2003 年 4 月 14 日、佐々木様から、補正宣誓書への署名をなぜしなけりばいけないかという、署名をなさりたくない旨の電話をいただきました。間日夕刻に、

佐々木様へ説明したい旨の連絡をさせていただきましたが、その後、ご返事をいただくことができませんでした。

そこでお手数をおかけいたしますが、重誓書にご署名の上、弊社まで返信していただけるのか、または重誓書に署名しない旨を弊社までご連絡いただければ有難く存じます。ご連絡いただければ、本件に関して、佐々木様にこれ以上のお手を煩わせることはないでしょう。弊社の希望として、佐々木様には、他の共同発明者の方と共に補充重誓書に署名していただきたく、ご検討よろしくお願い申し上げます。

破具

<連絡先>

〒571-8501

門真市大字門真1006番地

松下電器産業株式会社

R & D知的財産権センター 知財開発グループ

竹之内 茂雄

TEL:06-6900-9276

FAX:06-6907-8018

E-mail:[takenouchi.shigao@jp.panasonic.com](mailto:takenouchi.shigao@jp.panasonic.com)

<同封書類>

2003年2月24日付 佐々木様へのご署名依頼状	・・・	1通
2003年4月8日付 佐々木様へのご署名依頼状	・・・	1通
Reissue前の米国特許公報 (US5,767,845)	・・・	1通
最新の補充補正書	・・・	1通
補充再発行出願重誓書	・・・	1通

以上

August 31, 2004

To Mr. Ryoichi Sasaki  
5-3-207, Makino-Kitamachi,  
Hirakata-shi, Osaka

Shigeo Takenouchi  
R&D Intellectual Property Center  
Matsushita Electric Industrial Co., Ltd.

Dear Mr. Sasaki,

I am writing to you about the matter on which I sent correspondence to you in the spring of 2003, regarding a reissue application for U.S. patent serial number 5,767,845 for which Mr. Sasaki is a co-inventor, identified as:

U.S. Patent Application Serial No. 09/587,107

Title of the Invention: Multi-Media Information Record  
Device and a Multi-Media Information Playback  
Device

Application Date: June 2, 2000

Matsushita Serial No. P12792-02

Japanese Agent Serial No. FP-95040a

U.S. Agent Serial No. 52478-0900 (AS70r)

In regards with the above-identified case, we received a request from the USPTO to submit an Amendment to the Reissue Application Declaration. This is for amending the Declaration you signed on June 21, 2000 together with the other inventors.

The original Declaration included an inadvertent error. That is to say, Claim 26 was mistakenly written as Claim 25. For your information, I enclose a copy of a recently prepared Supplemental Amendment that shows current claims, and also enclose a copy of the Amendment to the Reissue Application Declaration

prepared to correct this inadvertent error. As you may know, the U.S. Patent Serial No. 5,767,845 was issued in 1998 when you were a worker of our company. The reissue application is filed for the purpose of correcting the error in the U.S. Patent. That is to say, at present, we seek revision of the existing patent, not a new patent.

I sent a letter to you by registered mail on February 24, 2003, enclosing a copy of the U.S. Patent. It was certified that this letter had been delivered to you on February 25, 2003.

We sent correspondence to you several times in the spring of 2003. And on April 14, 2003, we received a phone call from you asking specifically what personal advantage you were to gain as an ex-employee if you agreed to sign the Declaration, giving us what appeared to be a negative answer concerning the signing.

In the same evening, I made a phone call to you and left a message on your answering machine requesting a meeting so that I could explain the circumstances to you in person. You have returned no phone call since then.

We would be grateful if you could let us know whether you could return us the Declaration signed by you or you will not sign the Declaration. After we receive a reply from you, we would never trouble you regarding this matter. We hope that you sign the Amendment to the Reissue Application Declaration together with the other inventors. Thank you for your consideration.

\*\*\*\*\*

Please contact to:

Shigeo Takenouchi

Intellectual Property Development Group, R&D Intellectual  
Property Center,

Matsushita Electric Industrial Co., Ltd.

1006, Kadoma, Kadoma-City, Osaka 571-8501

TEL: 06-6900-9276 FAX: 06-6907-8018

E-mail: [takenouchi.shigeru@ip.panasonic.com](mailto:takenouchi.shigeru@ip.panasonic.com)

Enclosed Documents

- \* A copy of our letter dated February 24, 2003 to Mr. Sakaki requesting to sign Reissue Application Declaration
- \* A copy of our letter dated April 8, 2003 to Mr. Sakaki requesting to sign Reissue Application Declaration
- \* A copy of published U.S. Patent Serial Number: 5,767,845 (before reissue)
- \* A copy of recently prepared Supplemental Amendment
- \* A copy of Amendment to the Reissue Application Declaration

2003年4月8日

佐々木 充一 様

松下電器産業株式会社

R&amp;D企画室 知財・法務グループ 知財第五チーム

竹之内 茂雄

Reissue Application Declaration へのご署名依頼の件

拝啓 時下ますますご清栄のこととお慶び申し上げます。

さて、佐々木様には2003年2月24日付の書留にて郵送させていただいた  
添付の書状の件です。佐々木様には、ご多忙中のところ何度も連絡させていただ  
き、申し訳ありません。弊社の都合にて佐々木様のお手を煩わすこととなります  
が、Reissue Application Declaration への佐々木様の署名をいただきたく、再度  
連絡させていただきました。

最終の米国特許庁への提出期限が4月25日に迫っており、それまでに何とか  
連絡を取らせていただきたく、まことにお手数ですが、本状を受け取られました  
ら、下記宛にご一報いただけないでしょうか。よろしくお願いいたします。ご参  
考までに佐々木様が共同発明者になられている米国登録特許公報を同封いたしま  
す。

敬具

## 記

## &lt;本案件&gt;

USP 特許番号 : US 5, 7 6 7, 8 4 5 (1998/06/16)

発明の名称 : マルチメディア処理方法及び装置

発明者 : 大蘆雅弘、楠見雄規、河合真宏、川原千尋、佐々木亮一

## &lt;連絡先&gt;

松下電器産業株式会社 R &amp; D企画室

知財・法務グループ 知財第五チーム 竹之内 茂雄

〒571-8501 大阪府門真市大字門真 1006 番地

E-mail: [takenouchi.shigeo@jp.panasonic.com](mailto:takenouchi.shigeo@jp.panasonic.com)

TEL: 06-6900-9278 FAX: 06-6907-8018

## &lt;同封書類&gt;

2003 年 2 月 24 日付 佐々木様へのご署名依頼状 . . . 1 通

Reissue 前の米国特許公報 (US5,767,845) . . . 1 通

以上



April 8, 2003

To Mr. Ryoichi Sasaki

Shigeo Takenouchi  
Intellectual Property 5<sup>th</sup> Team,  
Intellectual Property/Justice Group, R&D Planning Office,  
Matsushita Electric Industrial Co., Ltd.

Request to Sign Reissue Application Declaration

Dear Mr. Sasaki,

I am writing to you about the matter mentioned in our previous letter sent to you by registered mail, dated February 24, 2003.

I am sorry to keep you posted when you are so busy, but would appreciate it if you could sign the Reissue Application Declaration.

It is getting close to April 25, 2003 which is the final due date for filing. I hope that you will understand our position and would be grateful if you could contact us as indicated below upon reception of this letter. We enclose the published U.S. patent for which Mr. Sasaki is a co-inventor, for your reference.

\*\*\*\*\*

U.S. Patent Serial Number: 5,767,845 (1998/06/16)

Title of the Invention: Multi-Media Information Record Device  
and a Multi-Media Information Playback Device

Inventors: Masahiro Oashi, Yuki Kusumi, Masahiro Kawai, Chihiro  
Kawahara, Ryoichi Sasaki

Please contact to:

Shigeo Takenouchi

Intellectual Property 5<sup>th</sup> Team, Intellectual Property/Justice

Group, R&D Planning Office  
Matsushita Electric Industrial Co., Ltd.  
1006, Kadoma, Kadoma-City, Osaka 571-8501  
TEL: 06-6900-9276 FAX: 06-6907-8018  
E-mail: takenouchi.shigeru@ip.panasonic.com

Enclosed Document

- \* A copy of our letter dated February 24, 2003 to Mr. Sakaki requesting to sign Reissue Application Declaration
- \* A copy of published U.S. Patent Serial Number: 5,767,845 (before reissue)

2003年2月24日

佐々木 亮一 様

松下電器産業株式会社

R&amp;D企画室 知財・法務グループ 知財第五チーム

竹之内 茂雄

Reissue Application Declaration へのご署名依頼の件

拝啓 時下ますますご清栄のこととお慶び申し上げます。突然の書状をお送りして申し訳ありません。

さて、佐々木様が弊社開発本部情報通信研究所にご在職中に共同発明者となられてた下記発明に対し、Reissue Application Declaration への佐々木様の署名をいただく必要が生じてまいりました。Reissue とは、一度米国にて登録になった特許に対し、クレーム追加等で再度審査にかけるもので、本願の場合、登録となったクレームに不要な限定があるとの理由で、米国特許庁に再度審査をしてもらっています。ところが、登録時のクレームに新たな発明を追加するのですから、再度発明者の方にご自分の発明に対する宣言をしていただくことが必要となります。そこで、米国特許庁の指示から Reissue Application Declaration を提出するようにとの指示を受けました。

佐々木様は既に弊社を退社されておりますので、佐々木様と連絡を取らせていただきたく、本特許出願時の住所に郵送にて照会の連絡をさせていただいたしだいです。別途、佐々木様には、佐々木様のご友人である吉井様を経由して、2003年1月23日と2月18日の2回、E-mail を送付させていただきましたが、まだご返事をいただいております。このため以前のご住所にお住まいか否かを確認させていただきたく、本連絡をさせていただきました。

つきましては、まことにお手数ですが、本状を受け取られましたら、下記宛にご一報いただけないでしょうか。よろしくお願いいたします。ご参考までに佐々木様が共同発明者になられている米国登録特許公報を同封いたします。

敬具

## 記

## &lt;本案件&gt;

USP 特許番号 : US 5, 7 6 7, 8 4 5 (1998/06/16)

発明の名称 : マルチメディア処理方法及び装置

発明者 : 大庭雅弘、楠見雄規、河合眞宏、川原千尋、佐々木亮一

## &lt;連絡先&gt;

松下電器産業株式会社 R &amp; D企画室

知財・法務グループ 知財第五チーム 竹之内 茂雄

〒571-8501 大阪府門真市大字門真1006番地

E-mail: [takenouchi.shigeo@jp.panasonic.com](mailto:takenouchi.shigeo@jp.panasonic.com)

TEL: 06-6900-9278 FAX: 06-6907-8018

## &lt;同封書類&gt;

Reissue 前の米国特許公報 (US5,767,845) . . . 1通

以上

Translation of DOCUMENT 1
---------------------------

February 24, 2003

To Mr. Ryoichi Sasaki

Matsushita Electric Industrial Co., Ltd.  
R&D Planning Office, Intellectual Property/Justice Group,  
Intellectual Property 5<sup>th</sup> Team  
Shigeo Takenouchi

Request to Sign Reissue Application Declaration

Dear Mr. Sasaki,

Please forgive us to send this letter suddenly.

We are now required to have your signature on the Reissue Application Declaration which is to be submitted in regard with the invention on which you took part as a co-inventor while you worked for Matsushita Electric Industrial Co., Ltd. In general, reissue applications are filed to the USPTO when the applicants desire to add claims to patents that have been issued, or for some other reasons. The reissue applications are subjected to the examination procedure. In the case of the present reissue application, we filed it in the USPTO for the reason that we

had found unnecessary limitations in the claims, and it is currently examined. We received an instruction from the USPTO to submit the Reissue Application Declaration signed by the inventors. This is required since we are going to add new claims to the original claims of the patent.

You resigned after the application for the invention was filed.

We send this letter to the address that was the same as the one when the application was filed. In parallel with this, we sent you e-mails via Mr. Yoshii who is a friend of yours, on January 23, 2003 and February 18, 2003, but we have not received a reply from you. We accordingly send this letter hoping that you are living in the same residence as before.

Please contact us as indicated below if you succeeded to receive this letter. For your information we enclose the U.S. patent for which Mr. Sasaki is a co-inventor.

\*\*\*\*\*

U.S. Patent Serial Number: 5,767,845 (1998/06/16)

Title of the Invention: Multi-Media Information Record Device  
and a Multi-Media Information Playback Device

Inventors: Masahiro Oashi, Yuuki Kusumi, Masahiro Kawai, Chihiro  
Kawahara, Ryoichi Sasaki

Please contact to:

Matsushita Electric Industrial Co., Ltd.,

R&D Planning Office, Intellectual Property/Justice Group,

Intellectual Property 5<sup>th</sup> Team

Shigeo Takenouchi

〒571-8501

1006, Kadoma, Kadoma-City, Osaka

E-mail: takenouchi.shigeru@ip.panasonic.com

TEL: 06-6900-9276 FAX: 06-6907-8018

Enclosed Document

U.S. Patent Serial Number: 5,767,845

RECEIVED  
CENTRAL FAX CENTER

MAR 03 2005

PTO/SB/21 (06-02)

Approved for use through 01/01/2004, OMB nos 1-0002

U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

<b>REISSUE APPLICATION DECLARATION BY THE INVENTOR</b>	Docket Number (Optional) 63478-0900
<p>I hereby declare that:          Each inventor's residence, mailing address and citizenship are stated below next to their name.          I believe the inventors named below to be the original and first inventor(s) of the subject matter which is described and claimed in patent number <u>5,767,845</u>, granted <u>June 16, 1998</u> and for which a reissue patent is sought on the invention entitled <u>MULTI-MEDIA INFORMATION RECORD DEVICE AND A MULTI-MEDIA INFORMATION PLAYBACK DEVICE</u> the specification of which</p> <p><input type="checkbox"/> is attached hereto.</p> <p><input checked="" type="checkbox"/> was filed on <u>06/02/2000</u> as reissue application number <u>09/587,107</u> and was amended <u>11/21/2001, 06/06/2002, 09/24/2002, 04/29/2003, 11/17/2003.</u> (if applicable)</p> <p>I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.          I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.</p> <p><input type="checkbox"/> I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b). Attached is form PTO/SB/28 (or equivalent) listing the foreign applications.</p> <p>I verily believe the original patent to be wholly or partly inoperative or invalid, for the reasons described below. (Check all boxes that apply.)</p> <p><input type="checkbox"/> by reason of a defective specification or drawing.</p> <p><input checked="" type="checkbox"/> by reason of the patentee claiming more or less than he had the right to claim in the patent.</p> <p><input checked="" type="checkbox"/> by reason of other errors.</p> <p>At least one error upon which reissue is based is described below. If the reissue is a broadening reissue, such must be stated with an explanation as to the nature of the broadening:</p> <p>Claims 1, 4, 7, 25 and 26 define page information as "successively" stored in a storage area, while the prior art did not require such a description and therefore the patentee claimed less than they had a right to claim.</p> <p>Claim 19 defines "successively" regarding time sequence information in a storage area, while the prior art did not require such a description and therefore the patentee claimed less than they had a right to claim.</p> <p>Claim 7 is amended to replace "disc" with --recording medium--.</p>	

(Page 1 of 5)

This collection of information is required by 37 CFR 1.175. The information is required to obtain or retain a benefit by the public which is to be paid by the USPTO to process an application. Confidentiality is governed by 35 U.S.C. 422 and 37 CFR 1.14. This collection is estimated to take 30 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form should be submitted to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1489, Alexandria, VA 22313-1489. DO NOT SEND FEE OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1489, Alexandria, VA 22313-1489.

If you need assistance in completing the form, call 1-800-PTO-0198 and select option 2.



PTO/BB/61 (08-03)

Approved for use through 01/31/2004, OMB 0864-0032

U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

(REISSUE APPLICATION DECLARATION BY THE INVENTOR, page 2)		Docket Number (Optional) 53473-0900	
All errors corrected in this reissue application arose without any deceptive intention on the part of the applicant. As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this			
Name(s)		Registration Number	
Joseph W. Price, Reg. No. 28124		Ketan Vakil, Reg. No. 43218	
Alvin H. Goss, Reg. No. 24726		David J. Zostrow, Reg. No. 45258	
Julia Lera, Reg. No. 47758		and other attorneys or agents associated with Customer Number 21611	
Correspondence Address: Direct all communications about the application to:			
<input checked="" type="checkbox"/> Customer Number		21611	
OR			
<input type="checkbox"/> Firm or	Joseph W. Price		
Address	SWELL & WELMER LLP		
Address	1920 Main Street, Suite 1208		
City	Irvine	State	CA Zip 92614
Country	USA		
Telephone	949-253-6720	Fax	949-253-3307
I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine and imprisonment, or both, under 18 U.S.C. 1001, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this declaration is directed.			
Full name of sole or first inventor (given name, family name) Masahiro Oashi			
Inventor's signature		Date	
<i>Masahiro Oashi</i>		8/31/2004	
Residence Osaka, Japan		Citizenship Japan	
Mailing Address 43-22, Nomuramatsumachi, Hirakata-shi, Osaka 573-01 Japan			
Full name of second joint inventor (given name, family name) Yoshi Kusumi			
Inventor's signature		Date	
<i>Yoshi Kusumi</i>		8/31/2004	
Residence Kashiba, Japan		Citizenship Japan	
Mailing Address 3-15-40, Sakyakita, Kashiba-shi, Nara 639-02 Japan			
Full name of third joint inventor (given name, family name) Masahiro Kawai			
Inventor's signature		Date	
<i>Masahiro Kawai</i>		8/31/2004	
Residence Osaka, Japan		Citizenship Japan	
Mailing Address 7-33, Kanou, Himachii-Osaka-shi, Osaka 578 Japan			
<input checked="" type="checkbox"/> Additional joint inventors or legal representative(s) are named on separately numbered sheets forms PTO/BB/02A or 02LR attached			

[Page 2 of 3]

**RECEIVED  
CENTRAL FAX CENTER**

**MAR 03 2005**

PTO/SB/02A (04-22)

Approved for use through 07/01/2006. OMB 0571-0032

Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1996, no persons are required to respond to a collection of information unless it carries a valid OMB control number.

**DECLARATION****ADDITIONAL INVENTOR(S)**

Supplemental Sheet

52478-0700

Page 3 of 3

Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle if any)		Family Name or Surname	
Chihiro		Kawahara	
Inventor's Signature	<i>Chihiro Kawahara</i>		Date 8/31/2004
Residence: City	Ozaka	State	Country Japan
Citizenship Japan			
Mailing Address 44-21-405, Ishihara-cho, Kadoma-shi			
Mailing Address			
City	Ozaka	State	ZIP 571
Country Japan			
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle if any)		Family Name or Surname	
Ryoichi		Sasaki	
Inventor's Signature			Date
Residence: City	Ozaka	State	Country Japan
Citizenship Japan			
Mailing Address	5-3 1544 木様 御署名 akatsa-shi		
Mailing Address			
City	Ozaka	State	ZIP 573
Country Japan			
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle if any)		Family Name or Surname	
Inventor's Signature			Date
Residence: City		State	Country
Citizenship			
Mailing Address			
Mailing Address			
City		State	ZIP
Country			

This collection of information is required by 35 U.S.C. 118 and 37 CFR 1.62. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 24 minutes to complete, including reviewing, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form under suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1480, Alexandria, VA 22303-1480. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1480, Alexandria, VA 22303-1480.

If you need assistance in completing the form, call 1-800-PTO-0100 (1-800-706-0100) and select option 2.

Patent  
52478-0900

**IN THE CLAIMS:**

- 1           1.     (Original) A multi-media information playback device which plays back multi-  
2     media a disc information [recorded in a recording medium] comprising:
- 3                 (a)     a [disc] recording medium having pieces of page information, each of  
4     which is made up of multi-media information that describes contents of a plurality of screen  
5     images, [successively] stored in a storage area, the page information including:
- 6                     (1)     a partial image list having a pair of partial image information  
7                     showing a partial image of a screen image and display state information showing  
8                     display state of the partial image, and
- 9                     (2)     control information which describes a command to be executed  
10                    according to an input signal, including a display state change command  
11                    instructing to change the display state of the partial image;
- 12                 (b)     a page information read means for reading a piece of page information  
13     from the [disc] recording medium;
- 14                 (c)     a display data creation means for creating display data of the screen image  
15     by placing the partial image shown by the partial image information on a screen;
- 16                 (d)     a display means for displaying each display data created by the display  
17     data creation means;
- 18                 (e)     an input means for receiving an input signal from an operator; and
- 19                 (f)     a command execution means for detecting the input signal inputted by the  
20     operator, judging whether the input signal corresponds to the command described by the control  
21     information the page information read by the page information read means, and instructing the  
22     display data creation means to create new display data by changing the display state of the

Patent:  
52478-0900

23 corresponding partial image according to the display state change command when the input  
24 signal corresponds to the display state change command;  
25 wherein the display data creation means creates new display data according to the  
26 command execution means.

1 2. (Original) The multi-media information playback device of claim 1, wherein the  
2 page information includes:

3 (a) the partial image list;

4 (b) the control information including an animation display command  
5 instructing to change and display the display state information of the partial image corresponding  
6 to elapsed time; and

7 (c) time sequence control information including animation control  
8 information which describes values of the display state information of the partial image  
9 corresponding to the elapsed time;

10 wherein the command execution means includes:

11 (a) a first timer for measuring the elapsed time after start of activation;  
12 and

13 (b) an animation display command execution unit for activating the  
14 first timer when an input signal corresponding to the animation display command  
15 is detected, calculating values of the display state information corresponding to  
16 the elapsed time of each of the partial images based on the animation control  
17 information at predetermined times, instructing the display data creation means to  
18 create new display data by changing the display state of the partial image

Patent  
52478-0900

19 according to the calculated values of the display state information, and stopping  
20 the first timer when execution of the animation display command is completed;  
21 wherein the display data creation means creates new display data according to the  
22 animation display command execution unit.

1 3. (Original) The multi-media information playback device of claim 2, wherein the  
2 page information includes:

3 (a) the partial image list having a pair of the partial image information and  
4 display state information, the display state information including X-Y coordinates showing a  
5 display position of the partial image to be displayed on the screen, X-Y enlargement rates  
6 showing a ratio of size of the partial image shown by the partial image information and a partial  
7 image to be displayed on the screen, and a rotational angle between the partial image shown by  
8 the partial image information and a partial image to be displayed on the screen; and

9 (b) time sequence control information including the animation control  
10 information which describes at least one among the values of the X-Y coordinates, the X-Y  
11 enlargement rates, and the rotational angle corresponding to the elapsed time;

12 wherein the animation display command execution unit includes:

13 (a) an X-Y coordinates calculation unit for calculating the X-Y  
14 coordinates corresponding to the elapsed time based on the animation control  
15 information at predetermined times;

16 (b) an X-Y enlargement rate calculation unit for calculating the X-Y  
17 enlargement rates corresponding to the elapsed time based on the animation  
18 control information at predetermined times; and

Patent  
52478-0900

19 (c) a rotational angle calculation unit for calculating the rotational  
20 angle corresponding to the elapsed time based on the animation control  
21 information at predetermined times.

1 4. (Original) The multi-media information playback device of Claim 3, wherein  
2 there is at least one storage area on the [disc] recording medium for [successively] storing page  
3 information and at least one storage area for [successively] storing time sequence information,  
4 the page information including:

5 (a) the partial image list,

6 (b) the control information including a time sequence processing start  
7 command instructing to start execution of time sequence processing corresponding to the elapsed  
8 time, and

9 (c) time sequence control information including time sequence processing  
10 control information having a name of time sequence information to be played back according to  
11 the time sequence processing start command, IDs showing contents of the time sequence  
12 information to be played back at predetermined times, and playback state information describing  
13 how the time sequence information should be played back in accordance with display of the  
14 partial image shown by the partial image information in the partial image list;

15 wherein the time sequence information has information, which should be played  
16 back according to the elapsed time, stored in order of playback;

17 wherein the command execution means includes:

18 (a) a second clock unit for measuring the elapsed time after the start of  
19 activation; and

Patent  
52478-0900

(b) a time sequence processing execution unit for activating the second clock means when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second clock unit when playback of the time sequence information is completed;  
wherein the multi-media information playback device further includes:

(a) a page storage means, which is implemented by RAM, for storing the page information read by the page information read means;

(b) a time sequence information read means for reading the time sequence information designated by the time sequence processing execution unit from the [disk] recording medium; and

(c) a playback means for playing back the time sequence information read by the time sequence information read means, and instructing the display means to display the time sequence information.

5. (Original) The multi-media information playback device of claim 4, wherein the page information includes:

(a) the partial image list,

(b) the control information, and

(c) time sequence control information including time sequence processing control information having a name of first time sequence information as time sequence information to be played back according to the time sequence processing start command, IDs of sound information to be played back at predetermined times, and playback state information

Patent  
52478-0900

9 which describes how sound information should be played back in accordance with display of the  
10 partial image shown by the partial image information in the partial image list;  
11 wherein the time sequence information includes the first time sequence  
12 information comprising sound information corresponding to the ID of sound information, the  
13 sound information being divided into equal predetermined sizes and placed in order of playback  
14 corresponding to the elapsed time;  
15 wherein the time sequence processing execution unit includes a first time  
16 sequence processing execution unit for designating the sound information in the first time  
17 sequence information corresponding to the elapsed time at predetermined times, when a name of  
18 the first time sequence information is shown by the time sequence processing control  
19 information;  
20 wherein the playback means includes a sound playback unit for playing back the  
21 sound information.

1 6. (Original) The multi-media information playback device of claim 4, wherein the  
2 page information includes:  
3 (a) the partial image list,  
4 (b) the control information, and  
5 (c) the time sequence control information including a name of a second time  
6 sequence information as time sequence information to be played back according to the time  
7 sequence processing start command, pairs of IDs of sound information and image information to  
8 be played back at predetermined times, and the playback state information which describes at



Patent:  
52478-0900

9 least one of dynamic picture and animation should be displayed in an area relating to the partial  
10 image shown by the partial image information;

11 wherein the time sequence information includes the second time sequence  
12 information comprising sound information divided into equal predetermined sizes and image  
13 information showing an image of at least one of the dynamic picture and the animation, the  
14 sound information and the image information being placed in order of playback corresponding to  
15 the elapsed time;

16 wherein the time sequence processing execution unit includes a second time  
17 sequence processing execution unit for designating sound information and image information in  
18 the second time sequence information corresponding to the elapsed time at predetermined times  
19 when the second time sequence information is shown by the time sequence processing control  
20 information, and instructing the display data creation means to create new display data by  
21 placing the partial image read by the time sequence information read means in an area shown by  
22 the playback state information;

23 wherein the display data creation means creates new display data according to the  
24 second time sequence processing execution unit.

1 7. (Currently Amended) A multi-media information record device for recording  
2 multi-media information in a [disc] recording medium, comprising:

3 (a) a partial image storage means for storing the partial image information of  
4 at least one partial image in one partial image file, the partial image information being a part of  
5 the screen image;

Patent  
52478-0900

6 (b) a partial image list input means for receiving input of a name of at least  
7 one partial image file in the partial image storage means and display state information showing  
8 display state of the partial image shown by the partial image information in the partial image file;

9 (c) a page information storage means for having a plurality of separate small  
10 storage areas, each of which is used for storing at least a piece of page information which is  
11 made up of multi-media information that describes contents of a plurality of screen images;

12 (d) a partial image list write means for writing a pair of the partial image  
13 information and the display state information in a first small storage area in the page information  
14 storage means along with the Ids of the partial image information and the display state  
15 information, after reading partial image information from the partial image file whose name is  
16 inputted, the display state information being inputted according to the partial image information;

17 (e) a control information input means for receiving input of control  
18 information which includes a name of input signal and display state change command instructing  
19 to change display state of the partial image corresponding to the input signal;

20 (f) a control information write means for writing the inputted control  
21 information in a second small storage area in the page information storage means; and

22 (g) a page information record means for [successively] recording information,  
23 which is written as a piece of page information in each small storage area in the page information  
24 storage means, in a storage area on the [disc] recording medium.

1 8. (Original) The multi-media information record device of claim 7, wherein the  
2 control information includes animation display command instructing to change and display state  
3 information of the partial image corresponding to the elapsed time;

Patent  
52478-0900

4                wherein the control information input means further includes an animation display  
5    command input unit for receiving input of a pair of an input signal and the animation display  
6    command;

7                wherein the multi-media information record device further includes:

8                (a)    a time sequence control information input means for receiving time  
9                sequence control information including animation control information, the  
10               animation control information describing how display state of the partial image  
11               changes according to the elapsed time; and

12               (b)    a time sequence control information write means for writing the  
13               inputted time sequence control information in a third small storage area in the  
14               page information storage means.

1               9.    (Original) The multi-media information record device of claim 8, wherein the  
2    partial image list input means further includes a display state information input unit for receiving  
3    input of display state information for each piece of partial image information, the display  
4    information including X-Y coordinates showing a display position of the partial image to be  
5    displayed on the screen, X-Y enlargement rates showing a ratio of size of the partial image  
6    shown by the partial image information and a partial image to be displayed on the screen, and a  
7    rotational angle between the partial image shown by the partial image information and a partial  
8    image to be displayed on the screen;

9               wherein the time sequence control information input means receives input of  
10    animation control information which describes how at least one among the values of the X-Y

- Patent  
52478-0900

11 coordinates, the X-Y enlargement rates, and the rotational angle changes corresponding to the  
12 elapsed time.

1 10. (Original) A multi-media information playback device for reading multi-media  
2 information from a data server connected via a network and playing back the multi-media  
3 information, comprising:

4 (a) a page information read means for reading a piece of page information,  
5 which is made up of multi-media information that describes contents of a plurality of screen  
6 images, stored as one file from a data server connected via a network, the page information  
7 including:

8 (1) a partial image list having at least one pair of the partial image  
9 information showing a partial image of a screen image and display state  
10 information describing display state of the partial image, and

11 (2) control information which describes a command to be executed  
12 according to an input signal, including a display state change command  
13 instructing to change the display state of the partial image;

14 (b) a display data creation means for creating display data of the screen image  
15 by placing the partial image shown by the partial image information on a screen;

16 (c) a display means for displaying each display data created by the display  
17 data creation means;

18 (d) an input means for receiving an input signal from an operator; and

19 (e) a command execution means for detecting the input signal inputted by the  
20 operator, judging whether the input signal corresponds to the command described by the control

- Patent  
52478-0900

21 information in the page information read by the page information read means, and instructing the  
22 display data creation means to create new display data by changing the display state of the  
23 corresponding partial image according to the display state change command when the input  
24 signal corresponds to the display state change command;

25 wherein the display data creation means creates new display data according to the  
26 command execution means.

1 11. (Original) The multi-media information playback device of claim 10, wherein the  
2 page information including:

3 (a) the partial image list;

4 (b) the control information including the animation display instructing to  
5 change and display state information of the partial image corresponding to the elapsed time; and

6 (c) time sequence control information including animation control  
7 information which describes values of display state information of the partial image  
8 corresponding to the elapsed time;

9 wherein the command execution means includes:

10 (a) a first timer for measuring the elapsed time after start of activation;

11 and

12 (b) an animation display command execution unit for activating the  
13 first timer when an input signal corresponding to the animation display command  
14 is detected, calculating values of the display state information corresponding to  
15 the elapsed time of each of the partial images based on the animation control  
16 information at predetermined times, instructing the display data creation means to

Patent  
52478-0900

17 create new display data by changing the display state of the partial image  
18 according to the calculated values of the display state information, and stopping  
19 the first timer when execution of the animation display command is completed;  
20 wherein the display data creation means creates new display data according to the  
21 animation display command execution unit.

1 12. (Original) The multi-media information playback device of claim 11, wherein the  
2 page information including:

3 (a) the partial image list having of at least one pair of the partial image  
4 information and the display state information including X-Y coordinates showing a display  
5 position of the partial image to be displayed on the screen, X-Y enlargement rates showing a  
6 ratio of size of the partial image shown by the partial image information and the partial image to  
7 be displayed on the screen, and a rotational angle between the partial image shown by the partial  
8 image information and the partial image to be displayed on the screen;

9 (b) the control information including the animation display command; and

10 (c) time sequence control information including the animation control  
11 information which describes at least one among the values of the X-Y coordinates, the X-Y  
12 enlargement rates, and the rotational angle corresponding to the elapsed time;

13 wherein the animation display command execution unit includes:

14 (a) an X-Y coordinates calculation unit for calculating the X-Y  
15 coordinates corresponding to the elapsed time based on the animation control  
16 information at predetermined times;

- Patent  
52478-0900

- 17 (b) an X-Y enlargement rate calculation unit for calculating the X-Y  
18 enlargement rates corresponding to the elapsed time based on the animation  
19 control information at predetermined times; and  
20 (c) a rotational angle calculation unit for calculating the rotational  
21 angle corresponding to the elapsed time based on the animation control  
22 information at predetermined times.

1 13. (Original) The multi-media information playback device of claim 12, wherein the  
2 page information including:

- 3 (a) the partial image list;  
4 (b) the control information including a time sequence processing start  
5 command instructing to start execution of time sequence processing corresponding to the elapsed  
6 time; and  
7 (c) time sequence control information including time sequence processing  
8 control information having a name of time sequence information to be played back according to  
9 the time sequence processing start command, ids showing contents of the time sequence  
10 information to be played back at predetermined times, and playback state information describing  
11 how the time sequence information should be played back in accordance with display of the  
12 partial image shown by the partial image information in the partial image list;  
13 wherein the command execution means includes:  
14 (a) a second timer for measuring the elapsed time after the start of  
15 activation; and

Patent  
52478-0900

(b) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second timer when playback of the time sequence information is completed;

wherein the multi-media information playback device further includes:

(a) a page storage means, which is implemented by RAM, for storing the page information read by the page information read means;

(b) a time sequence information read means for reading contents of the time sequence information designated by the time sequence processing execution unit from the time sequence information stored as one file in the data server via a network, the time sequence information having contents in order of playback corresponding to the elapsed time and its name being included in the time sequence control information; and

(c) a playback means for playing back the time sequence information ready by the time sequence information read means, and instructing the display means to display the time sequence information.

14. (Original) The multi-media information playback device in claim 13, wherein the page information including:

(a) the partial image list;

(b) the control information; and



- Patent  
52478-0900

5 (c) time sequence control information including time sequence processing  
6 control information having a name of the first time sequence information as time sequence  
7 information to be played back according to the time sequence processing start command, sound  
8 information to be played back according to the elapsed time of the first time sequence  
9 information, and

10 playback state information describing how the sound information should be  
11 played back in accordance with display of the partial image shown by partial image information  
12 in the partial image list;

13 wherein the time sequence processing execution unit includes a first time  
14 sequence processing execution unit for designating the sound information in the first time  
15 sequence information corresponding to the elapsed time at predetermined times, when a name of  
16 the first time sequence information is shown by the time sequence processing control  
17 information;

18 wherein the time sequence information read means reads the sound information  
19 designated by first time sequence processing execution unit from the first time sequence  
20 information stored as one file in the data server, the first time sequence information describing  
21 the divided sound information in order of playback corresponding to the elapsed time and its  
22 name being included in the time sequence control information;

23 wherein the playback means includes a sound playback unit for playing back the  
24 sound information.

Patent  
52478-0900

1           15. (Original) The multi-media information playback device of claim 13, wherein the  
2 page information including:

3                   (a) the partial image list;

4                   (b) the control information; and

5                   (c) the time sequence control information including a name of the second time  
6 sequence information as time sequence information to be played back according to the time  
7 sequence processing start command, a pair of sound information and image information to be  
8 played back corresponding to the elapsed time of the second time sequence information, and  
9 playback state information which describes at least one of dynamic picture and animation should  
10 be displayed in the area relating to the partial image shown by the partial image information;

11                   wherein the time sequence processing execution unit includes a second time  
12 sequence processing execution unit for designating sound information and image information in  
13 the second time sequence information corresponding to the elapsed time at predetermined times  
14 when the second time sequence information is shown by the time sequence processing control  
15 information, and instructing the display data creation means to create new display data by  
16 placing the partial image read by the time sequence information read means in an area shown by  
17 the playback state information;

18                   wherein the time sequence information read means reads the sound information  
19 and the screen image information designated by the second time sequence processing execution  
20 unit from the second time sequence information stored as one file in the data server, the time  
21 sequence information describing the divided sound information in order of playback and the  
22 screen image information describing one screen image of at least one of motion picture and

-Patent  
52478-0900

23 animation corresponding to the elapsed time and its name being included in the time sequence  
24 control information;  
25 wherein the display data creation means creates new display data according to the  
26 second time sequence processing execution unit.

1 16. (Original) A multi-media information record device for recording multi-media  
2 information in a data server connected via a network, comprising:

3 (a) a partial image storage means for storing the partial image information of  
4 at least one partial image in one partial image file, the partial image information being a part of  
5 the screen image;

6 (b) a partial image list input means for receiving input of a name of at least  
7 one partial image file in the partial image storage means and display state information showing  
8 display state of the partial image shown by the partial image information in the partial image file;

9 (c) a page information storage means for having a plurality of separate small  
10 storage areas, each of which is used for storing at least a piece of page information which is  
11 made up of multi-media information that describes contents of a plurality of screen images;

12 (d) a partial image list write means for writing a pair of the partial image  
13 information and the display state information in a first small storage area in the page information  
14 storage means along with the IDs of the partial image information and the display state  
15 information, after reading partial image information from the partial image file whose name is  
16 inputted, the display state information being inputted according to the partial image information;

Patent  
52478-0900

17 (e) a control information input means for receiving input of control  
18 information which includes a name of input signal and display state change command instructing  
19 to change display state of the partial image corresponding to the input signal;

20 (f) a control information write means for writing the inputted control  
21 information in a second small storage area in the page information storage means; and

22 (g) a page information record means for recording contents of a piece of page  
23 information in one file in the data server after transmitting contents written as a piece of page  
24 information in each storage area in the page information storage means to a data server along  
25 with its write request.

1 17. (Original) The multi-media information record device of claim 16, wherein the  
2 control information includes animation display command instructing to change and display state  
3 information of the partial image corresponding to the elapsed time;

4 wherein the control information input means further includes an animation display  
5 command input unit for receiving input of a pair of an input signal and the animation display  
6 command;

7 wherein the multi-media information record device further includes:

8 (a) a time sequence control information input means for receiving time  
9 sequence control information including animation control information, the  
10 animation control information describing how display state of the partial image  
11 changes according to the elapsed time; and

Patent:  
52478-0900

12 (b) a time sequence control information write means for writing the  
13 inputted time sequence control information in a third small storage area in the  
14 page information storage means.

1 18. (Original) The multi-media information record device of claim 17, wherein the  
2 partial image list input means further includes a display state information input unit for receiving  
3 input of display state information for each piece of partial image information, the display  
4 information including X-Y coordinates showing a display position of the partial image to be  
5 displayed on the screen, X-Y enlargement rates showing a ratio of size of the partial image  
6 shown by the partial image information and a partial image to be displayed on the screen, and a  
7 rotational angle between the partial image shown by the partial image information and a partial  
8 image to be displayed on the screen;

9 wherein the time sequence control information input means receives input of  
10 animation control information which describes how at least one among the values of the X-Y  
11 coordinates, the X-Y enlargement rates, and the rotational angle changes corresponding to the  
12 elapsed time.

1 19. (Original) A multi-media information record device for recording multi-media  
2 information in a disc, comprising:

3 (a) a partial image storage means for storing the partial image information of  
4 at least one partial image in one partial image file, the partial image information being a part of  
5 the screen image;

Patent  
52478-0900

6 (b) a partial image list input means for receiving input of a name of at least  
7 one partial image file in the partial image storage means and display state information showing  
8 display state of the partial image shown by the partial image information in the partial image file;

9 wherein the partial image list input means further includes a display state  
10 information input unit for receiving input of display state information for each piece of partial  
11 image information, the display information including X-Y coordinates showing a display  
12 position of the partial image to be displayed on the screen, X-Y enlargement rates showing a  
13 ratio of size of the partial image shown by the partial image information and a partial image to be  
14 displayed on the screen, and a rotational angle between the partial image shown by the partial  
15 image information and a partial image to be displayed on the screen;

16 (c) a page information storage means for having a plurality of separate small  
17 storage areas, each of which is used for storing at least a piece of page information;

18 (d) a partial image list write means for writing a pair of the partial image  
19 information and the display state information in a first small storage area in the page information  
20 storage means along with the Ids of the partial image information and the display state  
21 information, after reading partial image information from the partial image file whose name is  
22 inputted, the display state information being inputted according to the partial image information;

23 (e) a control information input means for receiving input of control  
24 information which includes a name of input signal and display state change command instructing  
25 to change display state of the partial image corresponding to the input signal;

26 wherein the control information includes animation display command instructing  
27 to change and display state information of the partial image corresponding to the elapsed time;

Patent  
52478-0900

wherein the control information input means further includes an animation display command input unit for receiving input of a pair of an input signal and the animation display command;

(f) a control information write means for writing the inputted control information in a second small storage area in the page information storage means;

(g) a page information record means for [successively] recording information, which is written as a piece of page information in each small storage area in the page information storage means, in a storage area on the disc;

(h) a time sequence control information input means for receiving time sequence control information including animation control information, the animation control information describing how display state of the partial image changes according to the elapsed time;

wherein the time sequence control information input means receives input of animation control information which describes how at least one among the values of the X-Y coordinates, the X-Y enlargement rates, and the rotational angle changes corresponding to the elapsed time;

(i) a time sequence control information write means for writing the inputted time sequence control information in a third small storage area in the page information storage means;

(j) a time sequence information storage means having a piece of time sequence information stored in each time sequence information file, the time sequence information having information written in order of playback corresponding to the elapsed time; and

Patent  
52478-0903

51 (k) a time sequence information record means for [successively] recording time  
52 sequence information in a storage area on the disc after receiving input of a name of at least one  
53 time sequence information file in the time sequence information storage means, reading time  
54 sequence information from the time sequence information file whose name is inputted, and  
55 correlating the time sequence information with a name of time sequence information  
56 corresponding to the name of the file;

57 wherein the control information input means further includes a time sequence  
58 processing start command input unit for receiving input of a pair of an input signal and a time  
59 sequence processing start command in the control information, the time sequence processing  
60 start command instructing to start execution of time sequence processing corresponding to the  
61 elapsed time and being included in the control information;

62 wherein the time sequence control information input means further includes a  
63 time sequence processing control information input unit for receiving input of the time sequence  
64 processing control information which includes a name of time sequence information to be played  
65 back according to the time sequence processing start command, data showing contents of the time  
66 sequence information to be played back at predetermined times, and playback state information  
67 which describes how the time sequence information should be played back in accordance with  
68 display of the partial image list, the time sequence processing control information being included  
69 in the time sequence control information.

1 20. (Original) The multi-media information record device of claim 19, wherein the  
2 time sequence information includes first time sequence information in which sound information



- Patent:  
52478-0900

3 is divided into predetermined equal data sizes, the sound information being written along with its  
4 ID in order of playback corresponding to the elapsed time;

5            wherein the time sequence information record means includes a first time  
6   sequence information record unit for recording first time sequence information in the disc after  
7   reading the first time sequence information from the time sequence information file, whose name  
8   is inputted, when a name of the first time sequence information is inputted; and

9                    wherein the time sequence processing control information input unit includes first  
10 time sequence processing control information input unit for receiving input of first time sequence  
11 processing control information which includes a name of first time sequence information to be  
12 played back according to time sequence processing start command of the page information, Ids  
13 of sound information to be played back at predetermined times, and playback state information  
14 which describes how the sound information should be played back in accordance with display of  
15 the partial image shown by the partial image information in the partial image list, the first time  
16 sequence control information being included in the time sequence processing control  
17 information.

21. (Original) The multi-media information record device of claim 19, wherein the time sequence information record means includes a second time sequence information record unit for recording second time sequence information in the disc after reading the second time sequence information from the time sequence information file, whose name is inputted, when a name of the second time sequence information is inputted, the second time sequence information having sound information divided into predetermined equal data sizes, image information showing one screen image of at least one of animation and dynamic picture and Ids of the sound

- Patent:  
52478-0900

8 information and the image information written in order of playback corresponding to the elapsed  
9 time; and

10 wherein the time sequence processing control information input unit includes a  
11 second time sequence processing control information input unit for receiving input of second  
12 time sequence processing control information which includes a name of second time sequence  
13 information to be played back according to time sequence processing start command of the page  
14 information, pairs of Ids of sound information and image information to be played back at  
15 predetermined times, and the playback state information describing at least one of dynamic  
16 picture and animation should be displayed in an area relating to partial image shown by the  
17 partial image information in the partial image list.

1 22. (Original) A multi-media information record device for recording multi-media  
2 information in a data server connected via a network, comprising:

3 (a) a partial image storage means for storing the partial image information of  
4 at least one partial image in one partial image file, the partial image information being a part of  
5 the screen image;

6 (b) a partial image list input means for receiving input of a name of at least  
7 one partial image file in the partial image storage means and display state information showing  
8 display state of the partial image shown by the partial image information in the partial image file;

9 (c) a page information storage means for having a plurality of separate small  
10 storage areas, each of which is used for storing at least a piece of page information which is  
11 made up of multi-media information that describes contents of a plurality of screen images;

Patent  
52478-0900

12 (d) a partial image list write means for writing a pair of the partial image  
13 information and the display state information in a first small storage area in the page information  
14 storage means along with the Ids of the partial image information and the display state  
15 information, after reading partial image information from the partial image file whose name is  
16 inputted, the display state information being inputted according to the partial image information;

17 wherein the partial image list input means further includes a display state  
18 information input unit for receiving input of display state information for each piece of partial  
19 image information, the display information including X-Y coordinates showing a display  
20 position of the partial image to be displayed on the screen, X-Y enlargement rates showing a  
21 ratio of size of the partial image shown by the partial image information and a partial image to be  
22 displayed on the screen, and a rotational angle between the partial image shown by the partial  
23 image information and a partial image to be displayed on the screen;

24 (e) a control information input means for receiving input of control  
25 information which includes a name of input signal and display state change command instructing  
26 to change display state of the partial image corresponding to the input signal;

27 wherein the control information includes animation display command instructing  
28 to change and display state information of the partial image corresponding to the elapsed time;

29 wherein the control information input means further includes an animation display  
30 command input unit for receiving input of a pair of an input signal and the animation display  
31 command;

32 (f) a control information write means for writing the inputted control  
33 information in a second small storage area in the page information storage means;

Parent  
52478-0900

34 (g) a page information record means for recording contents of a piece of page  
35 information in one file in the data server after transmitting contents written as a piece of page  
36 information in each storage area in the page information storage means to a data server along  
37 with its write request;

38 (h) a time sequence control information input means for receiving time  
39 sequence control information including animation control information, the animation control  
40 information describing how display state of the partial image changes according to the elapsed  
41 time;

42 wherein the time sequence control information input means receives input of  
43 animation control information which describes how at least one among the values of the X-Y  
44 coordinates, the X-Y enlargement rates, and the rotational angle changes corresponding to the  
45 elapsed time;

46 (i) a time sequence control information write means for writing the inputted  
47 time sequence control information in a third small storage area in the page information storage  
48 means;

49 (j) a time sequence information storage means having a piece of time  
50 sequence information stored in each time sequence information file, the time sequence  
51 information having information written in order of playback corresponding to the elapsed time;  
52 and

53 (k) a time sequence information record means for recording contents of time  
54 sequence information in one file in the data server for each piece of time sequence information,  
55 after receiving a name of at least one time sequence information file in the time sequence  
56 information storage means, reading time sequence information from the time sequence

Patent:  
52478-0900

57 information file whose name is inputted, correlating the time sequence information with a name  
58 of time sequence information corresponding to the file, and transmitting the time sequence  
59 information to the data server along with its write request;

60 wherein the control information input means further includes a time sequence  
61 processing start command input unit for receiving input of a pair of an input signal and a time  
62 sequence processing start command in the control information, the time sequence processing  
63 start command instructing to start execution of time sequence processing corresponding to the  
64 elapsed time and being included in the control information; wherein the time sequence control  
65 information input means further includes a time sequence processing control information input  
66 unit for receiving input of the time sequence processing control information which includes a  
67 name of time sequence information to be played back according to the time sequence processing  
68 start command, IDs showing contents of the time sequence information to be played back at  
69 predetermined times, and playback state information which describes how the time sequence  
70 information should be played back in accordance with display of the partial image shown by the  
71 partial image information in the partial image list, the time sequence processing control  
72 information being included in the time sequence control information.

1 23. (Original) The multi-media information record device of claim 22, wherein the  
2 time sequence information includes first time sequence information in which sound information  
3 is divided into predetermined equal data sizes, the sound information being written along with its  
4 ID in order of playback corresponding to the elapsed time; wherein the time sequence  
5 information record means includes a first time sequence information record unit for recording  
6 first time sequence information in the disc after reading the first time sequence information from

52478.0900PRICE/NAV314073.1

Patent  
52478-0900

7 the time sequence information file, whose name is inputted, when a name of the first time  
8 sequence information is inputted; wherein the time sequence processing control information  
9 input unit includes first time sequence processing control information input unit for receiving  
10 input of first time sequence processing control information which includes a name of first time  
11 sequence information to be played back according to time sequence processing start command of  
12 the page information, IDs of sound information to be played back at predetermined times, and  
13 playback state information which describes how the sound information should be played back in  
14 accordance with display of the partial image shown by the partial image information in the  
15 partial image list, the first time sequence control information being included in the time sequence  
16 processing control information.

1 24. (Original) The multi-media information record device of claim 22, wherein the  
2 time sequence information record means includes a second time sequence information record  
3 unit for recording second time sequence information in the disc after reading the second time  
4 sequence information from the time sequence information file, whose name is inputted, when a  
5 name of the second time sequence information is inputted, the second time sequence information  
6 having sound information divided into predetermined equal data sizes, image information  
7 showing one screen image of at least one of animation and dynamic picture and IDs of the sound  
8 information and the image information written in order of playback corresponding to the elapsed  
9 time;

10 wherein the time sequence processing control information input unit includes a  
11 second time sequence processing control information input unit for receiving input of second  
12 time sequence processing control information which includes a name of second time sequence

Patent  
52478-0900

13 information to be played back according to time sequence processing start command of the page  
14 information, pairs of Ins of sound information and image information to be played back at  
15 predetermined times, and the playback state information describing at least one of dynamic  
16 picture and animation should be displayed in an area relating to partial image shown by the  
17 partial image information in the partial image list.

1 25. (Original) A multi-media information playback device which plays back multi-  
2 media information recorded in a recording medium comprising:

3 (a) a disc having pieces of page information [successively] stored in a storage  
4 area, each piece of page information being made up of multi-media information that describes  
5 contents of a plurality of screen images, the page information including:

6 (1) a partial image list having a pair of partial image information  
7 showing a partial image of a screen image and display state information showing  
8 display state of the partial image,

9 (2) control information which describes a command to be executed  
10 according to an input signal, the control information including:

11 a display state change command instructing to change the display  
12 state of the partial image;

13 an animation display command instructing to change and display  
14 the display state information of the partial image corresponding to elapsed  
15 time; and

16 a time sequence processing start command instructing to start  
17 execution of time sequence processing corresponding to the elapsed time;

- Patent  
52478-0900

18 (3) time sequence control information having information,  
19 which should be played back according to the elapsed time, stored in order  
20 of playback, the time sequence control information including:

21 (a) animation control information which describes  
22 values of the display state information of the partial image  
23 corresponding to the elapsed time; and

24 (b) time sequence processing control information  
25 having a name of time sequence information to be played back  
26 according to the time sequence processing start command, IDs  
27 showing contents of the time sequence information to be played  
28 back at predetermined times, and playback state information  
29 describing how the time sequence information should be played  
30 back in accordance with display of the partial image shown by the  
31 partial image information in the partial image list;

32 (b) a page information read means for reading a piece of page information  
33 from the disc;

34 (c) a display data creation means for creating display data of the screen image  
35 by placing the partial image shown by the partial image information on a screen;

36 (d) a display means for displaying each display data created by the display  
37 data creation means;

38 (e) an input means for receiving an input signal from an operator; and

39 (f) a command execution means for detecting the input signal inputted by the  
40 operator, judging whether the input signal corresponds to the command described by the control



Patent  
52478-0900

information in the page information read by the page information read means, and instructing the display data creation means to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command; the command execution means including:

(1) a first timer for measuring the elapsed time after start of activation;

(2) an animation display command execution unit for activating the first timer when an input signal corresponding to the animation display command is detected, calculating values of the display state information corresponding to the elapsed time of each of the partial images based on the animation control information at predetermined times, instructing the display data creation means to create new display data by changing the display state of the partial image according to the calculated values of the display state information, and stopping the first timer when execution of the animation display command is completed;

(3) a second timer for measuring the elapsed time after the start of activation; and

(4) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second timer when playback of the time sequence information is completed;

wherein the display data creation means creates new display data according to the animation display command execution unit;

Patent  
52478-0900

- 64 (g) a page storage means, which is implemented by RAM, for storing the page  
65 information read by the page information read means;
- 66 (h) a time sequence information read means for reading the time sequence  
67 information designated by the time sequence processing execution unit from the disk; and
- 68 (i) a playback means for playing back the time sequence information read by  
69 the time sequence information read means, and instructing the display means to display the time  
70 sequence information.

1 26. (Original) A multi-media information playback device which plays back multi-  
2 media information recorded in a recording medium comprising:

3 (a) a disc having pieces of page information [successively] stored as one file  
4 from a data server connected via a network, each piece of page information being made up of  
5 multi-media information that describes contents of a plurality of screen images, the page  
6 information including:

7 (1) a partial image list having a pair of partial image information  
8 showing a partial image of a screen image and display state information showing  
9 display state of the partial image,

10 (2) control information which describes a command to be executed  
11 according to an input signal, the control information including:

12 a display state change command instructing to change the display  
13 state of the partial image;

Patent  
52478-0900

14 an animation display command instructing to change and display  
15 the display state information of the partial image corresponding to elapsed  
16 time; and

17 a time sequence processing start command instructing to start  
18 execution of time sequence processing corresponding to the elapsed time;

19 (3) time sequence control information having information, which  
20 should be played back according to the elapsed time, stored in order of playback,  
21 the time sequence control information including:

22 (a) animation control information which describes values of  
23 the display state information of the partial image corresponding to the  
24 elapsed time; and

25 (b) time sequence processing control information having a  
26 name of time sequence information to be played back according to the  
27 time sequence processing start command, IDs showing contents of the  
28 time sequence information to be played back at predetermined times, and  
29 playback state information describing how the time sequence information  
30 should be played back in accordance with display of the partial image  
31 shown by the partial image information in the partial image list;

32 (b) a page information read means for reading a piece of page information  
33 from the disc;

34 (c) a display data creation means for creating display data of the screen image  
35 by placing the partial image shown by the partial image information on a screen;

Patent  
52478-0900

(d) a display means for displaying each display data created by the display data creation means;

(e) an input means for receiving an input signal from an operator; and

(f) a command execution means for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information in the page information read by the page information read means, and instructing the display data creation means to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command; the command execution means including:

(1) a first timer for measuring the elapsed time after start of activation;

(2) an animation display command execution unit for activating the first timer when an input signal corresponding to the animation display command is detected, calculating values of the display state information corresponding to the elapsed time of each of the partial images based on the animation control information at predetermined times, instructing the display data creation means to create new display data by changing the display state of the partial image according to the calculated values of the display state information, and stopping the first timer when execution of the animation display command is completed;

(3) a second timer for measuring the elapsed time after the start of activation; and

(4) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start

Patent  
52478-0900

59                   command is detected, designating contents of the time sequence information  
60                   corresponding to the elapsed time, and stopping the second timer when playback  
61                   of the time sequence information is completed;  
62                   wherein the display data creation means creates new display data according to the  
63 animation display command execution unit;  
64                   (g)     a page storage means, which is implemented by RAM, for storing the page  
65 information read by the page information read means;  
66                   (h)     a time sequence information read means for reading the time sequence  
67 information designated by the time sequence processing execution unit from the time sequence  
68 information stored as one file in the data server via a network, the time sequence information  
69 having contents in order of playback corresponding to the elapsed time and its name being  
70 included in the time sequence control information; and  
71                   (i)     a playback means for playing back the time sequence information read by  
72 the time sequence information read means, and instructing the display means to display the time  
73 sequence information.



US005767845A

## United States Patent (19)

Oashi et al.

(11) Patent Number: 5,767,845

(45) Date of Patent: Jan. 16, 1998

[54] MULTIMEDIA INFORMATION RECORD  
DEVICE, AND A MULTI-MEDIA  
INFORMATION PLAYBACK DEVICE

\$292,500 1/1997 Edwards et al. 398,778

## FOREIGN PATENT DOCUMENTS

328644 of 0000 Japan  
3314228 of 0000 Japan  
6346580 of 0000 Japan  
670113 of 0000 Japan

## OTHER PUBLICATIONS

MacroModel, MacroMedia, Chapter 4, pp. 147-161,  
178-195 May, 1993.

Primary Examiner—Joseph H. Feld  
Assistant Examiner—Joe-Ho Choi  
Attorney, Agent, or Firm—Price, Goss & Ubell

[75] Inventors: Masahiro Oashi, Hirokazu, Yuki  
Kusumai, Kazuhisa; Masahiro Kawai,  
Hiroshi-Osaka; Chihito Kawabata,  
Moriguchi; Ryoschi Sasaki, Hirokazu,  
all of Japan

[73] Assignee: Matsushita Electric Industrial Co.,  
Osaka, Japan

[21] Appl. No.: 512,343

[22] Filed: Aug. 4, 1995

[30] Foreign Application Priority Data

Aug. 10, 1994 JP Japan 6-188424  
Aug. 4, 1995 JP Japan 7-197907

[51] Int. Cl. G06T 1/00

[52] U.S. Cl. 345/342; 345/475

[56] Field of Search 395/173, 806  
395/807, 174, 175; 345/473-475, 302

[56] References Cited

## U.S. PATENT DOCUMENTS

3,510,210 5/1970 Honey 382/39  
4,951,229 1/1990 DiNocella et al. 393/173  
5,208,384 5/1993 Nishiyama 345/123  
5,314,733 5/1993 Ohta et al. 345/426  
5,333,063 10/1994 Yoshizawa et al. 345/426  
5,383,182 10/1994 Langan et al. 395/174  
5,428,723 6/1995 Adams et al. 395/174  
5,459,830 10/1995 Ohta et al. 395/173  
5,502,570 3/1996 Shikama et al. 386/25  
5,546,390 10/1996 Silverbrook 395/173

## [37] ABSTRACT

A CD-ROM 201 for recording multi-media information of at least one page stream. Contents of each page stream are successively recorded in the storage areas in the CD-ROM 201. The following three items are shown by the page stream: a partial image list having at least one pair of partial image data which describes partial images of one screen image and display state information including X-Y coordinates, X-Y enlargement rates and a rotation angle showing the display state; control information which describes command to be executed corresponding to an input signal; time line information which describes parameters concerning time sequence processing to be executed corresponding to the control information. The display data creation unit 213 synthesizes partial images shown by the partial image list and creates display data from the partial image data and display state information in the page stream read from the CD-ROM 201, and writes the display data in the display data storage unit 209.

24 Claims, 19 Drawing Sheets

Partial Image List	
Partial Image ID	101, 102
X-Y coordinates	101, 102
X-Y enlargement rates	101, 102
Rotation angle	101, 102
Partial Image Data	101, 102
Display State Information	
Display State ID	101, 102
X-Y coordinates	101, 102
X-Y enlargement rates	101, 102
Rotation angle	101, 102
Partial Image Data	101, 102
Control Information	
Control Command A	101, 102
Control Command B	101, 102
Control Command C	101, 102
Time Line Information	
Time Line ID	101, 102
Time Line Data	101, 102
Time Line Data	101, 102
Time Line Data	101, 102


U.S. Patent

Jun. 16, 1998

Sheet 1 of 19

5,767,843

**FIG. 1**  
**PRIOR ART**




U.S. Patent

Jun. 16, 1998

Sheet 2 of 19

5,767,845






U.S. Patent

Jun. 16, 1998

Sheet 3 of 19

5,767,845

FIG. 3




U.S. Patent

Jun. 16, 1998

Sheet 4 of 19

5,767,845

FIG. 4




U.S. Patent

Jun. 16, 1998

Sheet 5 of 19

5,767,845

FIG. 5




U.S. Patent

Jun. 16, 1998

Sheet 6 of 19

5,767,845

FIG. 6




U.S. Patent

Jun. 16, 1998

Sheet 7 of 19

5,767,845

FIG. 7






U.S. Patent

Jun. 16, 1998

Sheet 8 of 19

5,767,845

FIG. 8

partial image list	
partial image ID	1
X-Y coordinates	100, 100
X-Y enlargement rates	1, 1
rotational angle	0
partial image data	
partial image ID	2
X-Y coordinates	120, 120
X-Y enlargement rates	1, 1
rotational angle	0
partial image data	
partial image ID	3
X-Y coordinates	150, 150
X-Y enlargement rates	1, 1
rotational angle	0
partial image data	

control information	
input signal A	X-Y coordinates of partial image 1 should be (170,100)
input signal B	Start the time line clock
input signal C	Read page stream 2

time line information			
00:00	00:01	00:02	00:03
X-Y coordinates animation : partial image ID3			
150,150	170,170	190,150	
time line stream : 1			
dynamic picture display object : partial image ID3			

U.S. Patent

Jun. 16, 1993

Sheet 9 of 19

5,767,845

FIG. 9(a)




FIG. 9(b)




FIG. 9(c)




FIG. 9(d)



FIG. 9(e)





FIG. 9(f)




U.S. Patent

Jun. 16, 1998

Sheet 10 of 19

5,767,845

FIG. 10






U.S. Patent

Jan. 16, 1998

Sheet 11 of 19

5,767,845

FIG. 11

partial image list	
partial image ID	1
X-Y coordinates	100, 100
X-Y enlargement rates	1, 1
rotational angle	0
partial image data	

control information	
input signal A	X-Y coordinates of partial image 1 should be (200,200)

time line information			
00:00	00:01	00:02	00:03


U.S. Patent

Jun. 16, 1998

Sheet 12 of 19

5,767,845

FIG. 12




U.S. Patent

Jul. 16, 1998

Sheet 13 of 19

5,767,845

FIG. 13




U.S. Patent

Jun. 16, 1998

Sheet 14 of 19

5,767,845




U.S. Patent

Jun. 16, 1998

Sheet 15 of 19

5,767,845

FIG. 15




U.S. Patent

Jun. 16, 1998

Sheet 16 of 19

5,767,845




U.S. Patent

Jun. 16, 1998

Sheet 17 of 19

5,767,845

FIG. 17




U.S. Patent

Jun. 16, 1998

Sheet 18 of 19

5,767,845

FIG. 18






U.S. Patent

Jun. 16, 1998

Sheet 19 of 19

5,767,845

FIG. 19



5,767,845

1  
MULTI-MEDIA INFORMATION RECORD  
DEVICE, AND A MULTI-MEDIA  
INFORMATION PLAYBACK DEVICE  
BACKGROUND OF THE INVENTION

## (1) Field of the Invention

The present invention relates to a multi-media information record device and a multi-media information playback device. The multi-media information record device records multi-media information like dynamic/still picture, graphics, sound and the like in a storage device and a recording medium provided to a data server; the multi-media information playback device plays back the multi-media information inputted via a recording medium and a transmission line.

## (2) Description of the Related Art

Recently, TV game sets, electronic publications, quality karaoke sets and video on demand devices are used as read-only multi-media information playback devices. These multimedia information playback devices play back multi-media information recorded in a optical disc (CD-ROM) and a digital video disc (DVD), and also multi-media information transmitted from a data server via a network and the like.

The following explanation is about "Denshi Kamishibai-Electronic Picture-Card Show" disclosed in Japanese Laid-open Patent Application No. 3-22648, which is an example of the conventional multi-media information playback device mentioned above. FIG. 1 is an example of a data configuration of multi-media information of a conventional multi-media information playback device, by which images and sound are synchronously played back.

Data and information shown in a data area section and control information section of FIG. 1 are recorded in the recording medium like a digital disc. Control information shown in the control information section is recorded in each block composed of predetermined amount of data shown in the data area section. In which sound data and still picture data mingle. In the data area section of FIG. 1, An (n is a natural number) represents sound data; VnB and VnC represent still pictures A and B, respectively; CLUT (color look up table) represents CLUT data; NOPn represents data to which no operation is applied. In the control information section, (1) represents a data write command; (2) represents a CLUT data command; (3) represents a data display command; (4) represents an audio data command; (5) represents a command of no operation. In the screen image section, A and B represent still pictures A and B, respectively. Both of them are displayed on the screen.

Each command in the control information section is executed in order from the left side to the right side. First, audio data A1, which is digitalized sound information, is transferred to audio data memory by the control information (4), and outputted as an analog audio signal via an audio D/A (digital/analog) converter. Video data V1B is written in a predetermined position of video memory of V41B from V1B, after the write area of a still picture is designated by the control information (1). The CLUT data updates the screen image by the control information (2). Based on a CLUT memory, contents of the video memory are converted to an analog video signal by the video D/A converter, so that the contents are displayed on the screen. While the screen image and an audio signal A44 in FIG. 1 are synchronized, a still picture A can be switched to a still picture B. Although the succeeding still pictures C, D, E... are not shown in FIG. 1, the same processing is carried out to play back display screens and sound synchronously.

2

The next explanation is about a general playback processing of a multi-media information playback device. Multi-media information playback device places a line end signal and a page end signal, which are already inserted in the digitalized image signals, at the end of a scanning line (normally more than 500) and a page (contents of a screen at every 1/60 second) in the display device like Cathode Ray Tube and Liquid Crystal Display, respectively, and displays the scanning lines on the proper pages, so that image signals recorded in the recording medium like a CD-ROM and a DVD are displayed at predetermined positions on the screen of the display device. Multi-media information playback device quadruples a size of an image to be displayed on the screen by using two pixels vertically and horizontally, which forms the smallest square of four pixels. For each pixel in the display device, or by interpolation. This device also reduces an image to a quarter size, by clipping a pixel vertically and horizontally.

Also the multi-media information playback device poses an image to be displayed on the screen by converting coordinates of each pixel using trigonometric function. As pixels are more dense in the recording medium than in the display device, predetermined adjustment is applied to the recording medium so that a proper image is displayed based on the pixel density of the display device, in time of normal display. So practically, there's no problem when an image which is stored in the CD-ROM as a small still picture is enlarged as much as possible on the screen of the display unit.

Generally, the multi-media information playback device is equipped with necessary programs to play back the multi-media information stored in the recording medium. Sometimes, a different program is already written in the multi-media information so that commands which are added to the multi-media information or which are changed are executed according to the program. In this case, signs which are similar to "T" and "F" are given to the different program which is described by the multi-media information, so that the multimedia information playback device recognizes the program to be executed.

Moreover, the multi-media information playback device displays a still picture, which does not change at all during the display time, in the display device by repeating the steps of reading and displaying the display data stored in a VRAM (video RAM) every 1/60 second or so. On the other hand, dynamic pictures are displayed by repeating the steps of updating the display data stored in the VRAM, reading and displaying the updated display data every 1/60 second or so. Therefore, one storage unit of page data which shows each screen image of the display device is about 1/60 second for dynamic pictures.

Sound which is played back synchronously with the dynamic pictures can be delimited by 1/60 second or so and stored with each page data which consists the dynamic picture. Therefore, the multi-media information playback device is equipped with a storage unit which stores sound data of at least 1/60 second so that the sound is successively played back along with the dynamic pictures.

As for DVD, details can be found in the next reference: "Movies can be stored in a hard disc photo-electric magnetic and phase change", featured in Jul. 18, 1994 issue of "Nikkei Electronics No. 615", pages 76-81.

However, in the conventional art mentioned above, data about movies, sound, and their controlling, are stored separately. Specifically, in the case of image data, data for the whole screen image including the background is stored as

5.767,845

3

one still picture data. Therefore, when part of the screen image is changed by, e.g. moving a part of the still picture to a different position on the screen, enlarging or reducing a part of the still picture, more still picture data coping with the change has to be stored in the CD-ROM or the DVD. So the maximum number of the still pictures which can be displayed is limited by the storage capacity of the CD-ROM and the DVD. Moreover, each time the still picture data is displayed, they have to be read from the CD-ROM and the DVD, so the number of still pictures which can be displayed per unit time is limited by the data transfer rate between the CD-ROM or the DVD and a memory.

When the audio data, the still picture data, the dynamic picture data and the control information are stored in different storage areas, the multi-media information playback device has to access different storage areas of the CD-ROM or the DVD in order to read the control information and each data used for it every time it executes the control information. This results in bad read efficiency. Also, load of the multi-media information playback device for controlling the internal memory is large since data are separately read into the memory provided to the multi-media information playback device from the different storage areas of the CD-ROM and the DVD.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide a multi-media information playback device, in which readout of display data from a recording medium is not necessary each time a part of a screen image is changed and displayed, the display data can be created easily, and the load on a CPU controlling a memory is small.

The above object may be fulfilled by the multi-media information playback device which shows the following features.

(1) A multi-media information playback device which plays back multi-media information recorded in a recording medium comprises a disc having page information successively stored in a storage area, the page information including a partial image list having a pair of partial image information showing a partial image of a screen image and display state information showing display state of the partial image, and the page information also including control information which describes a command to be executed according to an input signal, the control information including a display state change command instructing to change the display state of the partial image; a page information read unit for reading the page information from the disc; a display data creation unit for creating display data of the screen image by placing the partial image shown by the partial image information on a screen; a display unit for displaying each display data created by the display data creation unit; an input unit for receiving an input signal from an operator; and a command execution unit for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information in the page information read by the page information read unit, and instructing the display data creation unit to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command; wherein the display data creation unit creates new display data according to the command execution unit.

According to the above construction, image information and display state of partial images constituting one screen

4

image are shown by the page information successively recorded in the storage area on the disc. So in time of changing and displaying a part of a screen image, what is needed is only creating display data by changing the display state of the corresponding partial image according to the control information. The display data can be changed easily in this way.

Also, a part of the screen image of display data can be changed only by the page information, so that the display data does not have to be read from the recording medium. So there is no need to record display data, whose part of the screen image is changed, in the recording medium beforehand. Therefore, the number of display data which can be displayed per unit time is not limited by the data transfer rate between the disc and the memory.

Moreover, information needed for changing and displaying only a part of the screen image using partial images is shown by the partial image list in one page information. So the load on a CPU which controls memory in the multi-media information playback device is small compared to the case in which necessary information is loaded to the memory of the multi-media information playback device. When a new image screen composed of different partial images in the multi-media information playback device is displayed, new page information which describes the partial images is read, and display data for showing that image screen is created from the page information. Therefore, new display data can be created by only one head seek which happens in time of reading new page information. Compared to the case in which partial image information is read from several places on the disc (which unit head seek happens several times), the readout of the partial image information can be carried out in short time. That means new image screen is displayed in shorter time than before.

(2) The page information may include the partial image list, the control information, and the time sequence control information including a name of a second time sequence information as time sequence information to be played back according to the time sequence processing start command, pairs of IDs of sound information and image information to be played back at predetermined times, and the playback state information which describes at least one of dynamic picture and caption should be displayed in an area relating to the partial image shown by the partial image information; wherein the time sequence information may include the second time sequence information comprising sound information divided into equal predetermined time and image information showing an image of at least one of the dynamic picture and the caption, the sound information and the image information being placed in order of playback corresponding to the elapsed time; wherein the time sequence processing execution unit may include a second time sequence processing execution unit for designating sound information and image information in the second time sequence information corresponding to the elapsed time at predetermined times when the second time sequence information is shown by the time sequence processing control information, and instructing the display data creation unit to create new display data by placing the partial image read by the time sequence information read unit in an area shown by the playback state information; wherein the display data creation unit may create new display data according to the second time sequence processing execution unit.

According to above construction, the time sequence information including the second time sequence information, which describes sound information and image information in order of playback corresponding to the elapsed time, is

3.767.845

3

stored successively in the storage area on the disc. So head seek does not happen when the sound information and image information are successively read corresponding to the elapsed time. Therefore, the multi-media information playback device can read the sound information and the image information at high speed, so breaks does not happen in sound, animation and/or dynamic pictures, while the multi-media information is played back.

(3) A multi-media information record device for recording multi-media information in a disc may comprise a partial image storage unit for storing the partial image information of at least one partial image in one partial image file, the partial image information being a part of the screen image; a partial image list input unit for receiving input of a name of at least one partial image file in the partial image storage unit and display state information showing display state of the partial image shown by the partial image information in the partial image file; a page information storage unit for having a plurality of separate small storage areas, each of which is used for storing at least a piece of page information; a partial image list write unit for writing a pair of the partial image information and the display state information in a first small storage area in the page information storage unit along with the IDs of the partial image information and the display state information, after reading partial image information from the partial image file whose name is inputted, the display state information being inputted according to the partial image information; a control information input unit for receiving input of control information which includes a name of input signal and display state change command instructing to change display state of the partial image corresponding to the input signal; a control information write unit for writing the inputted control information in a second small storage area in the page information storage unit; and a page information record unit for successively recording information, which is written as a piece of page information in each small storage area in the page information storage unit, in a storage area on the disc.

According to the above construction, the page information can be stored successively in the storage area on the disc. Effects mentioned above can be obtained from the multi-media information playback device which plays back multi-media information from the disc.

(4) A multi-media information playback device for reading multi-media information from a data server connected via a network and playing back the multi-media information may comprise a page information read unit for reading a piece of page information stored as one file from a data server connected via a network, the page information including a partial image list having at least one pair of the partial image information showing a partial image of a screen image and display state information describing display state of the partial image, and the page information also including control information which describes a command to be executed according to an input signal, the control information including a display state change command instructing to change the display state of the partial image; a display data creation unit for creating display data of the screen image by placing the partial image shown by the partial image information on a screen; a display unit for displaying such display data created by the display data creation unit; an input unit for receiving an input signal from an operator; and a command execution unit for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information in the page information read by the page information read unit, and instructing the display data creation unit to

6

create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command; wherein the display data creation unit may create new display data according to the command execution unit.

According to the above construction, effects mentioned above can be obtained when multi-media information is read from the data server connected via a network and played back.

(5) A multi-media information record device for recording multi-media information in a data server connected via a network may comprise a partial image storage unit for storing the partial image information of at least one partial image in one partial image file, the partial image information being a part of the screen image; a partial image list input unit for receiving input of a name of at least one partial image file in the partial image storage unit and display state information showing display state of the partial image shown by the partial image information in the partial image file; a page information storage unit for having a plurality of separate small storage areas, each of which is used for storing at least a piece of page information; a partial image list write unit for writing a pair of the partial image information and the display state information in a first small storage area in the page information storage unit along with the IDs of the partial image information and the display state information, after reading partial image information from the partial image file whose name is inputted, the display state information being inputted according to the partial image information; a control information input unit for receiving input of control information which includes a name of input signal and display state change command instructing to change display state of the partial image corresponding to the input signal; a control information write unit for writing the inputted control information in a second small storage area in the page information storage unit; and a page information record unit for recording contents of a piece of page information in one file in the data server after transmitting contents within as a piece of page information in each storage area in the page information storage unit to a data server along with its write request.

According to the above construction, each page information can be stored in individual file in the data server, and above effects can be obtained in the multi-media information playback device which reads and plays back multi-media information from the data server.

#### BRIEF DESCRIPTION OF THE DRAWINGS

These and other objects, advantages and features of the invention will become apparent from the following description thereof taken in conjunction with the accompanying drawings which illustrate a specific embodiment of the invention. In the drawings:

FIG. 1 is an example of data configuration of multi-media information, which is showing synchronous playback of images and sound in the conventional multi-media information playback device.

FIG. 2 is a block diagram showing functional construction of a multi-media information playback device 200 of the first embodiment of the present invention.

FIG. 3 is a block diagram showing hardware construction of the multi-media information playback device 200 shown in FIG. 2.

FIG. 4 shows how multi-media information is recorded in the CD-ROM 201, the multi-media information being

5,767,845

7

played back by the multi-media information playback device 244 of the present invention.

FIG. 5 shows data configuration of a page stream played back by the multi-media information playback device 244 of the present embodiment.

FIG. 6 shows data configuration of time line stream played back by the multi-media information playback device 244 of the present embodiment.

FIG. 7 is a flow chart showing procedure of playback of the multi-media information in the multi-media information playback device 244 of the present embodiment.

FIG. 8 shows contents of the page stream 1, which is a concrete example of the page stream shown in FIG. 5.

FIG. 9(a) shows contents of the initial image illustrated by a display data creation unit 212 based on the partial image list of the page stream 1 shown in FIG. 8.

FIG. 9(b) shows contents when an input signal "A" is inputted while the page stream 1 is executed.

FIG. 9(c) shows contents right after an input signal "B" is inputted while the image shown in FIG. 9(b) is displayed.

FIG. 9(d) shows contents at "00 minute 01.000 second", which is an elapsed time after the start of the execution of the time line information.

FIG. 9(e) shows contents at "00 minute 02.000 seconds", which is an elapsed time after the start of the execution of the time line information.

FIG. 9(f) shows contents of the initial image when the page stream 2 is loaded to the page storage unit 216.

FIG. 10 shows contents of a time line stream 1, which is a concrete example of the time stream shown in FIG. 6.

FIG. 11 shows contents of a page stream 2, which follows the page stream 1 shown in FIG. 8.

FIG. 12 is a block diagram showing construction of the multi-media information record device 1244 of the second embodiment of the present invention.

FIG. 13 is a block diagram showing hardware construction of the multi-media information 1244 shown in FIG. 12.

FIG. 14 is a flow chart showing procedure of the recording of the multi-media information in the multi-media information record device 1244 of the present embodiment.

FIG. 15 is a flow chart showing procedure of the recording processing of the multi-media information in the multi-media information record device 1244 of the present embodiment.

FIG. 16 is a block diagram showing construction of the multi-media information playback device 1644 of the third embodiment of the present invention.

FIG. 17 is a block diagram showing hardware construction of the multi-media information 1644 shown in FIG. 16.

FIG. 18 is a block diagram showing construction of the multi-media information record device 1844 of the fourth embodiment of the present invention.

FIG. 19 is a block diagram showing hardware construction of the multi-media information 1844 shown in FIG. 18.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

##### (Embodiment 1)

FIG. 2 is a block diagram showing functional construction of a multi-media information playback device 244 of Embodiment 1 of the present invention. FIG. 3 is a block diagram showing hardware construction of the multi-media information playback device 244 shown in FIG. 2.

8

As shown in FIG. 2, the multi-media information playback device 244 comprises a CD-ROM 241, a CD-ROM interface unit 242, an input unit 243, a control information execution unit 244, a clock unit 245, a page load unit 246, a time line control unit 247, a storage unit 248, a display unit 212, a display data creation unit 213, an audio D/A conversion unit 214, and an audio output unit 215. The storage unit 248 further comprises a display data storage unit 249, a page storage unit 216, and an audio data storage unit 211.

As shown in FIG. 3, the multi-media information playback device 244 comprises a CPU 341, a RAM 342, a system clock 343, a timer 344, a key board 345, a joy pad 346, an input device interface 347, a disc interface 348, a CD-ROM 349, a MPEG decoder 311, a sound D/A converter 312, a speaker 313, a graphics controller 314, a VRAM 315, an image D/A converter 316, and a CRT 317, as components of hardware. The CPU 341 comprises functions to control operations of each component of the multi-media information playback device 244, in addition to the functions which are explained as follows.

The CD-ROM 241 can be attached/detached to the multi-media information playback device 244. The following multi-media information is written by High Sierra Format ISO 9660 and the like.

FIG. 4 shows how multi-media information, which is played back by the multi-media information playback device 244 of the present embodiment, is stored in the CD-ROM 241. Storage areas 441, 442, and 443 of the CD-ROM 241 continue successively on the track, and data stored in each of the storage areas is read one after another as the CD-ROM 241 turns. A page stream 1, which is mainly composed of partial image data and mentioned later, is recorded in the storage area 441. A page stream 2, which is mainly composed of partial image data and shows the page following the page stream 1, is recorded in the storage area 442. A time line stream 1, which is mainly composed of data about dynamic pictures and animations relating to the page stream 1, is recorded in the storage area 443, and mentioned later. Data is read from the CD-ROM 241 while the page stream 1, the page stream 2, and the time line stream 1 are used as a logical unit, respectively. But they don't necessarily correspond to the physical unit of the CD-ROM 241, like a sector.

A page is an image to be displayed on the screen, which is displayed every 1/60 second or so. Each page stream is multi-media information which describes contents of a plurality of pages. Each of the pages is composed of one or a plurality of predetermined partial images. If the original partial image is the same as the partial image which is mentioned later by the page stream, a partial image can be enlarged/reduced or can be moved parallel/rotationally and one or a plurality of partial images can be deleted by the same page stream.

FIG. 5 shows data configuration of a page stream which is played back by the multi-media information playback device 244 of the present embodiment. A page stream consists of a partial image list, control information, and time line information. Each page stream is given an identification number.

In the partial image list, contents of each partial image consisting of one screen image is written: a partial image ID which designates a partial image; X-Y coordinates which show the initial position of the partial image when it is displayed in the page; X-Y enlargement rate which show the scale of enlargement or reduction when the partial image is first displayed in the page; a rotation angle between a

5,767,845

9

partial image shown by the partial image data and the partial image displayed is the page; and partial image data which is expressed by the values corresponding to the pixels of the partial image. The partial image ID is expressed by the number which shows order of placing the partial images in the display data, when display data of one screen image is created by the partial imager shown by the page stream. Therefore, when the display areas of the partial image partially overlap with each other, the partial image data corresponding to the pixels of the overlapping areas is updated by partial image data which has a greater partial image ID. So partial images are displayed according to the partial image ID, which means that the partial image having a greater partial image ID covers the preceding partial images. The partial image data shown by the page stream can be expressed by compressed and decoded bit map data and, if the partial image is geometrical graphic form, it can be expressed by graphic data. Also, the partial image does not necessarily have to be a graphic form. It can be a string showing an input request displayed on each menu screen. In this case, the string can be shown by a character code.

The control information describes commands to be executed by the multi-media information playback device 200 for the input signal from the input unit 203 while the page shown by the page stream is displayed. The commands are described for each input signal. The commands are: change the X-Y coordinates of the partial image; change the X-Y enlargement rates of the partial image; change the rotational angle of the partial image; load other page stream; start the execution of the time line information; overlap a plurality of partial images; display the color images in black and white; emphasize a specific color; change frequency of sound; and the like.

The time line information describes animation display and dynamic picture display: the animation display moves predetermined image pictures shown by the partial image list as time goes by; the dynamic picture display displays the dynamic pictures shown by the time line stream mentioned later. Specifically, as for the animation display, the following items are shown: a partial image ID of the partial image to be displayed in animation (animation object); X-Y coordinates which shows a predetermined display position at every given time after the start of the animation display of the partial image; and an animation display and time of the partial image. As for the dynamic picture display, the following items are shown: the identification number of the time line stream which shows images to be displayed in dynamic picture; and a start time and an end time of the dynamic picture display. Also, when the dynamic picture image is displayed inside the predetermined partial image shown by the partial image list, the partial image ID of the partial image which is displayed in dynamic picture is shown so that the dynamic picture is displayed in place of the predetermined partial image. The dynamic picture image shown by the time line stream mentioned later does not necessarily have to be displayed inside the predetermined partial image shown by the partial image list.

FIG. 6 shows data configuration of the time line stream which is played back by the multi-media information playback device 200 of the present embodiment. Identification numbers are given to each time line stream. As described already, dynamic pictures and animations are displayed by playback of the successive still pictures at every display time, which is every 1/60 second or so. In the time line stream shown in FIG. 6, still picture data expressed by the compressed and encoded bit map data is stored according to the order of the display, along with the audio data corresponding

10

to the still picture. Also the audio data is compressed, encoded, divided into predetermined equal parts corresponding to the display time of the still picture data, and played back successively while the still picture data corresponding to the audio data is displayed. Each display time can be expressed by the elapsed time after the start of the clock unit 205. When the clock 205 can measure the elapsed time from the start of the display for a plurality of time streams, the display time can be expressed by the elapsed time from the start of the execution of each time line stream.

Also the audio data and the still picture data do not necessarily have to be shown by the time line stream. For example, when the audio data shown by the time line stream is played back while the display picture is displayed by the partial image shown by the page stream, only audio data can be shown in the time line stream. Animations as well as dynamic pictures can be shown by this time line stream. So in order to distinguish these animations from the images displayed by the partial image shown by the page stream, a term "dynamic picture display" is used for the display of animations and dynamic pictures using the still picture data shown in the time line stream.

The CD-ROM interface unit 202 is implemented by the disc interface 304, and reads multi-media information into the multi-media information playback device 200 according to the instruction of the page load unit 206, the multi-media information being described by the page stream and the time line stream recorded in the CD-ROM 201.

The input unit 203 comprises the joy pad 306, the key board 305, and operation unit like a mouse, which is not illustrated, and receives input of instruction from a user via the input device interface 207. The input unit 203 outputs the input signal corresponding to the received input. For example, this unit 203 outputs the input signals A, B, and C, which correspond to the buttons A, B, and C in the joy pad 306, to the control information execution unit 204.

The control information execution unit 204 is implemented by the CPU 301. This unit 204 interprets and interactively executes control information shown by the page stream loaded to the page storage unit 210. Specifically, the control information execution unit 204 instructs the page load unit 206, the time line control unit 207, and the display data creation unit 223 to execute processing based on the instruction of the control information.

The clock unit 205 is implemented by the system clock 303 and the timer 304. Being activated by the time line control unit 207, the timer 304 measures the elapsed time from the execution start of the time line information with reference to the system clock 303. The clock unit 205 can be equipped with a plurality of the timers 304 so that the elapsed time from the start of the execution of each time line stream can be measured along with the elapsed time from the start of the execution of the time line information.

The page load unit 206 is implemented by the CPU 301. This unit 206 instructs the CD-ROM interface unit 202 to read out a predetermined page stream and load the page stream to the page storage unit 210, when the multi-media information playback device 200 is activated. This unit also instructs the CD-ROM interface unit 202 to read the designated page stream and the time line stream according to the instruction of the time line control unit 207 or the control information execution unit 204, and loads the page stream or the time line stream to the page storage unit 210.

The time line control unit 207 is implemented by the CPU 301, and starts the execution of the time line information described by the loaded page stream according to the control

5.767,845

11

Information execution unit 204. This unit 207 activates the clock unit 208 when the execution of the time line information is started. This unit 207 initializes the timer 204 of the clock unit 208 when the execution of the time line information is completed. In case each time line stream is equipped with the driver 204 which measures the elapsed time from the start of the execution, corresponding timer 204 is initialized when execution of each time line stream is completed.

The time line control unit 207 instructs the display data creation unit 213 to place designated partial images, carrying out the designated processing like enlarging/reducing and rotational migrating, at the designated position of the X-Y coordinates, according to the elapsed time from the start of the execution of the time line information measured by the clock unit 208 when the time line information which instructs animation display is executed.

The time line control unit 207 instructs the page load unit 206 to load the time line stream designated in the time line information to the page storage unit 210, when the time line information which instructs the dynamic picture display is executed. This unit 207 designates the still picture data corresponding to the elapsed time from the start of the execution of the time line information measured by the clock unit 208 and posts the designated still picture data to the display data creation unit 213. Then this unit 207 instructs the display data creation unit 213 to place the still picture data at the predetermined position, for example, inside the partial image designated in the time line information. At the same time, this unit 207 reads the audio data corresponding to the still picture data from the time line stream, and transfers the audio data to the audio data storage unit 211.

The display data storage unit 209 is implemented by the VRAM 315, and stores the display data of one screen page which is created by the display data creation unit 213.

The page storage unit 210 is implemented by the RAM 302, and stores the page stream and the time line stream read from the CD-ROM 201.

The audio data storage unit 211 is implemented by the RAM 302, and stores audio data which is divided into about 1/10 second sizes.

The display unit 212 is implemented by the image D/A converter device 316 and the CRT 317. This unit 212 reads the display data stored in the display data storage unit 209 every 1/10 second or so and displays it in the CRT. The image D/A converter 316 reads the display data from the VRAM 315, which is the display data storage unit 209, every 1/10 second or so, converts the display data to analog signals, and supplies them to the CRT 317. The CRT 317 displays the analog signals which are converted from the display data. In the present embodiment, the CRT 317 is used for the display unit 212, but a liquid crystal display LCD or a television which is connected to the multi-media information playback device 200 can substitute for the CRT 317. The contents of the display unit 212 can be printed on paper.

The display data creation unit 213 is implemented by the CPU 301, the MPEG decoder 311, and the graphic controller 314. This unit 213 creates display data of a whole screen of an entire image, using the partial images shown by the loaded page stream, when a new page stream is loaded to the page storage unit 210. According to the instruction of the control information execution unit 204, this unit 213 carries out the designated processing (e.g., moving X-Y coordinates, enlarging/reducing, rotational moving, etc.) for the partial images shown by the loaded page stream, and creates display data of a whole screen which shows a still image

12

using the partial images. According to the instruction of the time line control unit 207, the unit 213 carries out the designated processing mentioned above for the partial images shown by the loaded page stream, creates display data for animation display, and updates the display data for dynamic picture display, using the still picture data designated by the time line control unit 207 from the still picture data shown by the designated time line stream. At this point, the MPEG decoder 311 expands and decodes the image data which was compressed and encoded according to the MPEG, such as still picture data shown by the time line stream and partial image data shown by the page stream.

The audio D/A converter unit 214 is implemented by the MPEG decoder 311 successively and the sound D/A converter 312. The MPEG decoder 311 reads the audio data stored in the audio data storage unit 211, and expands and decodes the audio data, which is stored compressed and decoded according to the MPEG. The sound D/A converter 312 converts the decoded audio data into analog signals, and outputs them to the speaker 313. As well as the image data, the audio data does not necessarily have to be compressed and decoded according to the MPEG. The audio data can be compressed and decoded according to other format, or does not have to be compressed and decoded at all. Therefore, the MPEG decoder 311 can be substituted for other decoder. When audio data which is not compressed and decoded is treated, there's no problem without decoder.

The audio output unit 215 is implemented by the speaker 313 and converts analog signals from the audio D/A converter unit 214 to sound and outputs the sound.

Explanation about the procedure of the playback of multi-media information in the multi-media information playback device 200 follows next. It refers to a flow chart in FIG. 7, concrete examples of the page stream 1, the page stream 2 and the time line stream illustrated from FIGs. 8-11; and concrete examples of the contents displayed based on them.

FIG. 7 is a flow chart showing the procedure of the playback of multi-media information in the multi-media information playback device 200 of the present embodiment.

The page load unit 206 instructs the CD-ROM interface unit 202 to read a predetermined page stream, the page stream 1 mentioned later, from the CD-ROM 201, and loads the read page stream to the page stream storage unit 210. (Step 701).

The display data creation unit 213 creates display data of the initial image from each partial image shown by the partial image list of the loaded page stream (Step 702). The display data is transferred to the display data storage unit 209, stored there, read and displayed by the display unit 212 every 1/10 second or so.

FIG. 8 shows contents shown by the page stream 1, which is a concrete example of the page stream shown in FIG. 1. In the partial image list, a circle having a pattern of oblique lines inside, a triangle having a pattern of vertical dashed lines inside, and a rectangle having no pattern inside are shown by the bit map data or graphic data as partial image data, according to the order of the partial image IDs. Also the X-Y coordinates which shows the display position of the partial image, the X-Y enlargement rate of the partial image, and a rotational angle are shown. In case of a circle whose partial image ID is 1, bit map data shown by the partial image data is placed based on the X-Y coordinates (100, 100) by the display data creation unit 213 and display data is created with the enlargement rate being (1.1), and the rotational angle being 0. The display data of the triangle

5,767,845

13

and the rectangle whose partial image IDs are 2 and 3, respectively, is created in the same way mentioned above. So in the areas where each partial image overlaps, the partial image data having a small partial image ID is updated by the partial image data having a greater partial image ID.

FIG. 9(e) shows the contents of the initial image, which is illustrated by the display data creation unit 213, based on the partial image list of the page stream 1 illustrated in FIG. 8. As mentioned already, in the illustration processing of the display data creation unit 213, the partial image data having a smaller partial image ID is updated by the partial image data having a greater partial image ID in areas where each partial image overlaps. So, as illustrated in the initial image of the FIG. 9(e), partial images having a greater partial image ID are displayed on top of the layers of other partial images.

The control information execution unit 204 detects an input signal from the input unit 203, when the processing of Step 702 is completed (Step 703), and starts Step 704 when the input signal is not detected.

When the input signal is detected, the control information execution unit 204 identifies the input signal (Step 704), and judges whether the input signal is shown by the control information of the page stream (Step 705). When the input signal is not shown, the control information execution unit 204 starts Step 704.

The control information execution unit 204 executes the command which is described according to the input signal, when the identified input signal is judged to be shown by the control information of the page stream (Step 706). The display data creation unit 213 creates display data based on the execution result of the control information execution unit 204 (Step 707).

The following explanation is about the processing from Steps 705-707 in the multi-media information playback device 200, referring to concrete examples.

The control information execution unit 204 identifies an input signal, and reads the control information from the page stream 1 in FIG. 8, which is loaded to the page storage unit 210. The control information is shown as A, B, and C, so that the control information execution unit 204 can judge the type of the input signal.

The control information execution unit 204 executes a command "The X-Y coordinates of the partial image 1 should be (170, 100)". That is because when the identified input signal is A, it is shown by the control information. Specifically, the control information execution unit 204 passes parameters "partial image ID=1", and "X-Y coordinates (170, 100)" to the display data creation unit 213. The control information execution unit 204 instructs the display data creation unit 213 to create display data based on the parameters. The display data creation unit 213 creates the display data according to the instruction. FIG. 9(b) shows contents when input signal A is inputted while the page stream 1 is executed. The partial image 1 is moved from (100, 100) to (170, 100).

When the identified input signal is B, the control information execution unit 204 executes a command "The clock of the time line should be started.", which corresponds to the input signal B. Specifically, the control information execution unit 204 instructs the time line control unit 207 to start the execution of the time line information shown by the page stream 1. Then the time line control unit 207 activates the clock unit 205. The time line control unit 207 also reads the time line information from the page stream 1, and when there's a designated time line stream in the time line information which shows the dynamic picture display, the time line

14

control unit 207 instructs the page load unit 206 to load the time line stream. The time line control unit 207 further creates parameters mentioned later based on the time line information, and passes it to the display data creation unit 213, and it instructs the display data creation unit 213 to create display data based on the parameters.

As is shown in FIG. 8, time line information about the animation display and the dynamic picture display is shown by the page stream 1.

The following items are shown concerning the animation display: a partial image ID "3" of the partial image to be displayed in animation (animation subject); 00 minute 00.000 second as an animation display start time and 00 minute 03.000 seconds as an animation display end time, both of which are expressed by the elapsed time from the start of the execution of the time line information; XY coordinates (150, 150) at 00 minute 00.000 seconds, XY coordinates (170, 170) at 00 minute 01.000 seconds, XY coordinates (190, 150) at 00 minute 02.000 seconds, all of which show the display positions of the partial image 3 at predetermined elapsed times.

The following items are shown concerning the dynamic picture display: an identification number "1" of the time stream to be displayed in dynamic pictures; 00 minute 00.000 second as a dynamic picture display start time and 00 minute 03.000 seconds as a dynamic picture display end time, both of which are expressed by the elapsed time from the start of the execution of the time line information.

The time line control unit 207 instructs the page load unit 206 to load the time line stream 1 to the page storage unit 210. FIG. 10 shows contents of the time line stream 1, which is a concrete example of the time line stream shown in FIG. 6. Still picture data which shows the thing seen and audio data to be played back while the still picture data is displayed are shown by the time line stream, both of which correspond to each elapsed time between 00 minute 00.000 second and 00 minute 03.000 seconds.

When the identified input signal is C, the control information execution unit 204 executes a command "Read the page stream 2", which corresponds to the input signal C. Specifically, the identified input signal instructs the page load unit 206 to load the page stream 2 to the page storage unit 210. Then the page load unit 206 instructs the CD-ROM interface unit 202 to read the page stream 2, and loads the read page stream 2 to the page storage unit 210. The display data creation unit 213 creates display data based on the partial image list of the loaded page stream 2.

FIG. 11 shows contents of the page stream 2, which follows after the page stream 1 shown in FIG. 8. In FIG. 11, a rectangle having a pattern of oblique lines inside is shown by the partial image data as its map data, along with a partial image data ID "1", X-Y coordinates (100, 100), X-Y enlargement rates (1.1), a rotational angle "0". Also, a command for the input signal A "The X-Y coordinates of the partial image 1 should be (200, 200)" is described by the control information of the page stream 2. Therefore, when A is inputted while the page stream 2 is executed based on the partial image list mentioned above, the partial image 1 is placed at (200, 200) of the X-Y coordinates. A time line information is not shown by the page stream 2.

FIG. 9, (f) shows contents of the initial image when the page stream 2 is loaded to the page storage unit 210. The rectangle having oblique lines inside, which is shown by the partial image list of the page stream 2, is shown by X-Y enlargement rates (1.1), a rotational angle "0", and X-Y coordinates (100, 100).



3,767,845

15

The time line control unit 287 checks the clock unit 285 to see whether it is operating, when Step 707 finishes (Step 708). When the clock unit 285 is operating, the time line control unit 287 reads the elapsed time from the start of the execution of the time line information, which is measured by the clock unit 285 (Step 709).

The time line control unit 287 judges whether there is a partial image designated to be displayed in animation, by the elapsed time read from the clock unit 285 (Step 710). When there is such a partial image, the time line control unit 287 calculates X-Y coordinates, which shows the display position of the partial image, from the already designated X-Y coordinates which correspond to a predetermined elapsed time. Then the time line control unit 287 passes the calculated X-Y coordinates, X-Y enlargement rates, a rotational angle and a partial image ID of the partial image to the display data creation unit 213 as parameters. Then the time line control unit 287 instructs the display data creation unit 213 to create display data based on the parameters. The display data creation unit 213 creates display data based on the parameters, and updates the display data in the display data storage unit 209 (Step 711). When there's no designated partial image in Step 710, the time line control unit 287 starts Step 712.

For example, when the elapsed time in Step 709 is 00 minute 00.000 second, the animation display start time shown by the time line information is 00 minute 00.000 second. So the time line control unit 287 creates a partial image ID "3" and X-Y coordinates (150,150) at 00 minute 00.000 second as parameters for animation display, and passes them to the display data creation unit 213. Then the display data creation unit 213 moves the partial image 3 to the position designated by the parameter "the X-Y coordinates (150,150) at 00 minute 00.000 second", creates display data, and updates the display data in the display data storage unit 209.

Also, when an elapsed time is 00 minute 01.000 second in Step 709, the partial image 3, which is designated to be displayed in animation, exists. So the time line control unit 287 creates an animation display partial image ID "3", and X-Y coordinates (170,170) at 00 minute 01.000 second as parameters for animation display. Then this unit 287 passes them to the display data creation unit 213. The display data creation unit 213 moves the partial image 3 to (170,170) based on the parameters and creates display data, and updates the display data in the display data storage unit 209.

When the elapsed time is 00 minute 01.500 second, the time line control unit 287 calculates "X-Y coordinates (160,160) at 00 minute 01.500 second" which is interpolating between the X-Y coordinates (150,150) at 00 minute 01.000 second and X-Y coordinates (170,170) at 00 minute 01.000 second, and passes it to the display data creation unit 213. The display data creation unit 213 moves the partial image to the (160,160), creates display data and updates the display data in the display data storage unit 209.

Moreover, the time line control unit 287 judges whether there is a time line stream designating dynamic picture display, by the elapsed time read from the clock unit 285 (Step 712). When the designated time line stream exists, the time line control unit 287 designates the still picture data corresponding to the elapsed time read from the clock unit 285, and passes the data to the display data creation unit 213. Also the time line control unit 287 reads audio data corresponding to the still picture data from the time line stream and transfers that data to the audio data storage unit 211. The display data creation unit 213 reads the designated still

16

picture data from the designated time line stream and creates display data. After the time line control unit 287 updates the display data in the display data storage unit 209 (Step 713), this unit starts Step 703. If the designated time line stream does not exist in Step 712, the time line control unit 287 starts Step 703.

For example, when the elapsed time in Step 709 is 00 minute 00.000 second, the dynamic picture display start time shown by the time line information is 00 minute 00.000 second. So the time line control unit 287 creates identification number "1" of the time line stream, 00 minute 00.000 second of the still picture data, and the partial image ID "3" as parameter for the dynamic picture display corresponding to the elapsed time 00 minute 00.000 second from the start of the execution of the time line information, and passes them to the display data creation unit 213. At the same time, the time line control unit 287 reads audio data A1 from the time line stream 1, and transfers it to the audio data storage unit 211. The time line control unit 287 instructs the display data creation unit 213 to create display data based on the parameter. Then the display data creation unit 213 places the still picture data designated by the parameter "still picture data=00 minute 00.000 second" inside partial image 3, creates display data, and updates the display data in the display data storage unit 209.

FIG. 9(c) shows contents right after the input signal B is inserted while FIG. 9(b) is displayed. FIG. 9(c) shows a screen image created based on each parameter whose elapsed time measured by the clock unit 285 is 00 minute 00.000 second. The partial image 3 to be displayed in animation is displayed by "X-Y coordinates (150,150) at 00 minute 00.000 second", while the partial images 1 and 2 are displayed on the same position as FIG. 9(b), since their X-Y coordinates are not designated by parameters for animation display. Also, still picture data of "00 minute 00.000 second" in the time line stream 1 is displayed inside the partial image 3. At the same time, the audio data A1 is played back. The difference between the contents of the initial image shown in FIG. 9(a) and that of FIG. 9(c) is the position of the circle having a pattern of oblique lines. In the former case, the circle is shown by the X-Y coordinates (100,100); in the latter case, it is displayed by (170,100).

Moreover, when the elapsed time in Step 709 is 00 minute 01.000 second, the time line stream 1 designating dynamic picture display, exists. So the time line control unit 287 creates parameters "identification number of the time line stream=1", "still picture data=00 minute 01.000 second", and "partial image ID=0" corresponding to the elapsed time "00 minute 01.000 second" for dynamic picture display, and passes them to the display data creation unit 213. At the same time, the time line control unit 287 reads the audio data A1 corresponding to the elapsed time 00 minute 01.000 second, from the time line stream 1, and transfers the data to the audio data storage unit 211. The display data creation unit 213 places the still picture data of the "00 minute 01.000 second", which is read from the time line stream 1, inside the partial image 3 according to the parameters and creates display data.

FIG. 9(d) shows contents at 00 minute 01.000 second, which is the elapsed time from the start of the execution of the time line information. As shown in FIG. 9(d), the partial images 1 and 2 are displayed at the same positions as FIG. 9(b), but the partial image 3 is moved to the position of the X-Y coordinates (170,170), and the still picture data of "00 minute 01.000 second" is displayed inside the partial image 3. While this image is displayed, the audio data A1 is played back.

5,767,845

17

Moreover, FIG. 3 shows contents at the elapsed time, 00 minute 02.000 seconds. The partial images 1 and 2 are displayed at the same positions as they are displayed in FIG. 2(c), by the same processing mentioned above. The partial image 3 is moved to (190, 150), and a still picture data of "00 minute 02.000 seconds" are displayed inside it. While this still picture is displayed, the audio data A) is played back. X-Y coordinates for animation display for the partial image 3 after "00 minute 02.000 seconds" is not shown by the control information in the page stream 1. While animation display continues until "00 minute 03.000 seconds", the partial image 3 is displayed at the X-Y coordinates (190, 150). However, still picture data until "00 minute 03.000 seconds" are successively displayed inside the partial image 3, and the audio data is also played back at the same time.

As explained above, display of partial images can be changed easily according to the present embodiment, compared to the case in which contents of one screen is stored as one image data in the recording medium. Also, even though the contents are linked to the combinations of the partial images, maximum number of the still pictures to be displayed can be increased regardless of the storage capacity of the recording medium. In case of changing the display of the partial image shown by in the loaded page stream, as the image data does not have to be read from the recording medium, the multi-media information playback device 200 can display many still pictures per unit time, regardless of the transfer rate. The contents of each page stream and each time line stream is successively stored on the same track of the CD-ROM, so head seek does not happen when the information is successively read. Speed of data readout from the same page stream and the same time line stream is fast and breaks in the sound and dynamic pictures do not happen, so that the multi-media information is played back accurately. As the partial image list, the control information relating to the partial image, and the time line information are described by one page stream, the image data, control information, and dynamic information are loaded to the RAM 303 and the load of the CPU is decreased, unlike the case in which the information are recorded in the different storage areas in the recording medium.

In the present embodiment, the still picture data and the audio data shown by the time line stream are compressed and encoded according to the MPEG, and they are expanded and decoded by the MPEG decoder 311. But the still picture data, the audio data and the partial image data are not necessarily have to be compressed and encoded according to the MPEG. They can be compressed and encoded by other formats like VFW (Video for Windows) or QT (Quick Time). Therefore the MPEG decoder 311 can be substituted for decoders following other formats, or a decoder is not necessary at all in case only the data which is not compressed and encoded is dealt with.

In the present embodiment, the page load unit 206 loads the contents of the designated time line stream from the CD-ROM 201 to the page storage unit 210 at a time, when the execution of the time line information is started; the display data creation unit 213 reads the designated still picture data in the loaded time line stream and creates display data. However, the contents of the time line stream does not necessarily have to be loaded at a time. For example, the page load unit 206 can load the designated still picture data and audio data in the designated time line stream to the page storage unit 210 at each display time of the dynamic picture display, and the display data creation unit 213 can read the loaded still picture data from the page storage unit 210 and create display data, and the time line

18

control unit 207 can transfer the loaded audio data to the audio data storage unit 211. Generally, the amount of the compressed and encoded image data is large, so the data amount shown by one time line stream can be considered rather large. Therefore, considering the storage capacity of the RAM 303, which is necessary as the page storage unit 210, the page load unit 206 had better load the designated still picture data and audio data to the page storage unit 210 at each display time of the dynamic picture display. As the contents of the time line stream is successively stored on the same track, seek of a read head does not happen, even if the designated still picture data and audio data are loaded from the CD-ROM 201 at each display time. This enables displaying of dynamic pictures without breaks in sound and images.

In the present embodiment, the time line control unit 207 instructs the page load unit 206 to load the time line stream designated in the time line information in time of dynamic picture display; the page load unit 206 instructs the CD-ROM interface stream unit 202 to read the time line stream from the CD-ROM 201. But the time line stream does not necessarily have to be read in this way, and the time line control unit 207 can directly instruct the CD-ROM interface unit 202 to read the designated time line stream.

In the present invention, the display unit 212 displays each page every 1/60 second or so. But in order to display dynamic picture images of high quality, each page has to be displayed every 1/60 or 1/60 second or so. In this case, still picture data and audio data corresponding to the display time of every 1/60 second or 1/60 second from the start of the execution of the time line stream are shown.

In FIG. 4, the page stream and the time line stream correlating with each other, are stored successively in the storage areas on the track of the CD-ROM 201. The most important point is that contents of each page stream or each time line stream is stored successively on the same track; the contents of the page stream and the time line stream do not have to be correlating with each other. For example, only one of the page stream and the time line stream can be stored successively in the storage areas.

In the present embodiment, the CD-ROM 201 is explained as the recording medium, but other storage medium like DVD can substitute for the CD-ROM 201. Broader interpretation is possible the recording medium can be a transmission line like a communication line, or a storage device of a video server mentioned later. In the storage area, all information does not have to be stored in the form of digital data. Part of the data, e.g., audio data of the time line stream, can be analog data and can be stored divided. In this case, the multi-media information playback device 200 can be equipped with a storage unit of analog data instead of the audio data storage unit 211.

(Embodiment 2)

FIG. 12 is a block diagram of construction of a multi-media information record device 1200 of the second embodiment of the present invention. FIG. 13 is a block diagram of the hardware construction of the multi-media information record device 1200 shown in FIG. 12.

As shown in FIG. 12, the multi-media information record device 1200 comprises an input unit 1201, a stream creation unit 1202, a second storage unit 1203, a CD-ROM unit 1204 and a CD-ROM 1210. The second storage unit 1203 comprises a partial image storage unit 1204, a dynamic picture storage unit 1205, an audio storage unit 1206, a page stream storage unit 1207 and a time line stream storage unit 1208.

5,767,845

19

As shown in FIG. 13, elements of the hardware construction of the multi-media information record device 1200 is almost the same as the multi-media information playback device 300 shown in FIG. 3, except that the multi-media information record device 1200 does not comprise the joy pad 306 but comprises a hard disc 1310.

The input unit 1201 is implemented by a key board 1305 and an input device interface 1307. The input unit 1201 comprises a scanner and a video capture board, both of which are not illustrated. The scanner inputs printed still pictures as digitized still picture data. The video capture board inputs motion pictures from a connected video tape recorder as digitized dynamic picture data.

The stream creation unit 1202 is implemented by a CPU 1301. According to the processing procedure, this unit 1202 instructs a CRT 1317 to display a menu screen and an input request, and receives input of instruction and character information from an editor of multi-media information. According to the instruction, the stream creation unit 1202 reads a partial image file, a dynamic picture file and audio file corresponding to each instruction, from the partial image storage unit 1204, the dynamic picture storage unit 1205, and the audio storage unit 1206, respectively, and interactively creates the page stream and the time line stream shown in FIGS. 5 and 6. Input of the control information is carried out by a character input from the input unit 1201. The processing of the stream creation unit 1202 is explained later, by means of flow charts in FIGS. 14 and 15.

The second storage unit 1203 is implemented by a hard disc 1310. This unit comprises the partial image storage unit 1204, the motion picture storage unit 1205, the audio storage unit 1206, the page stream storage unit 1207, and the time line stream storage unit 1208.

The partial image storage unit 1204 stores one or a plurality of partial image file(s). One partial image is already cut out from material data for expressing a still picture. The partial image is shown by bit map data or graphic data which are compressed and encoded according to MPEG, and stored in each partial image file. Contents in each partial image file correspond to the partial image data of the page stream. When the material data is correlated with control information or other material data by editing, it constitutes multi-media information.

The dynamic picture storage unit 1205 stores one or a plurality of dynamic picture file(s). In the dynamic picture file, still picture data cut out from the material data of still pictures for expressing dynamic pictures are stored in order of the display time, corresponding to a predetermined display time.

The audio storage unit 1206 stores one or a plurality of audio file(s). Audio data divided into the amount of sound data, which corresponds to the length of time in which one still picture data is displayed, are stored in order of the display time.

The page stream storage unit 1207 stores the page stream created by the stream creation unit 1202.

The time line stream storage unit 1208 stores the time line stream created by the stream creation unit 1202.

The CD-ROM write unit 1209 is implemented by a disc interface 1308. According to the instruction of the input unit 1201, this unit 1209 reads the page stream and the time line stream from the page stream storage unit 1207 and the time line stream storage unit 1208, respectively, and stores them in the CD-ROM 1110.

FIGS. 14 and 15 show flow charts showing procedure of storing multi-media information in the multi-media information record device 1200 of the present invention. Steps 1413-1428 are shown in a flow chart in FIG. 15.

20

The stream creation unit 1202 initializes the identification number of the page stream and the time line stream to "1". (Step 1401)

The stream creation unit 1202 requests as input instructing whether contents to be described exist in the page stream. When the contents to be described exist in the page stream (Step 1402), the stream creation unit 1202 initializes the partial image ID "1" (Step 1403).

The stream creation unit 1202 further requests input instructing whether contents to be described exist as a partial image of the partial image ID exist. When the contents exist (Step 1404), the stream creation unit 1202 receives a name of the partial image file which shows the partial images (Step 1405). Also, the stream creation unit 1202 receives input of X-Y coordinates, X-Y enlargement rates and a rotational angle, each of which describing the display position, enlargement rate and rotational angle of the partial image on the initial screen of the page stream (Step 1406). The stream creation unit 1202 writes the partial image ID, X-Y coordinates, X-Y enlargement rates and the rotational angle in the storage area allocated to each item of the partial image ID of the page stream in the page stream storage unit 1207. Then the stream creation unit 1202 reads the partial image file, whose name is inputted, from the partial image storage unit 1204, and writes the contents of the file in the storage area allocated to each item of the partial image data having the partial image ID of the page stream in the page stream storage unit 1207 (Step 1407). Then, the stream creation unit 1202 increments the partial image ID (Step 1408), and goes back to Step 1404.

In Step 1404, when the contents to be described as the partial image of the partial image ID does not exist, the stream creation unit 1202 further requests input instructing whether the page stream has control information to be described. When the page stream has the control information (Step 1409), the stream creation unit 1202 receives input of a name of the input signal (Step 1410), and receives input of commands to be executed according to the name of the input signal (Step 1411). The stream creation unit 1202 writes the name of the inputted input signal and the commands in one working area of the storage area allocated to the items of the control information of the page stream in the page stream storage unit 1207 (Step 1412), and then goes back to Step 1409.

In Step 1409, when the contents to be described as the partial image of the control information do not exist, the stream creation unit 1202 further requests input instructing whether the page stream has animation display to be described. When the animation display exists (Step 1413), the stream creation unit 1202 receives input of the partial image ID of the partial image to be displayed in animation (Step 1414), and receives input of one or a plurality of types of animation (instructing how the partial image of the partial image ID should be displayed in animation (Step 1415)). The types of animation is chosen from "movement", "enlarge", "rotation", and the like. A parameter, which changes with the passage of time is designated according to the input of the type of animation. The stream creation unit 1202 requests input instructing whether a pair of a time and a value, both of which should be shown by the page stream, exists; the time being expressed by the elapsed time from the start of the execution of the time line information and the value corresponding to the types of inputted animation, and the time mentioned above. When the pair exists (Step 1416), the

5,767.845

21

stream creation unit 1282 receives the input (Step 1417). Specifically, as parameters corresponding to the time mentioned above, values of the X-Y coordinates, the X-Y enlargement rates, and the rotational angle are inputted for "movement", "enlargement", and "rotation", respectively.

In Step 1416, when the pair does not exist, the stream creation unit 1282 writes the partial image ID of the partial image to be displayed in animation and the pair of the time and the parameter in the now working area of the storage areas allocated to the information relating to the animation display of the page stream in the page stream storage unit 1287 (Step 1418), and goes back to Step 1413.

In Step 1413, when the animation display to be described does not exist in the page stream, the stream creation unit 1282 requests input instructing whether dynamic picture display to be described exists in the page stream. When the dynamic picture display to be described exists (Step 1419), the stream creation unit 1282 receives input of a start and end times of the dynamic picture display, and the partial image ID of the partial image which should be displayed in dynamic picture (dynamic picture display object) (Step 1420).

The stream creation unit 1282 further receives input of the name of the dynamic picture file which shows the dynamic picture to be displayed inside the partial image shown by the inputted partial image ID (Step 1421).

Next, the stream creation unit 1282 requests input instructing whether there is an audio file which shows sound to be played back synchronized with the dynamic picture shown by the name of the inputted file. When the audio file exists (Step 1422), the stream creation unit 1282 receives input of the name of the audio file (Step 1423). Next, the stream creation unit 1282 reads the dynamic picture file and the audio file from the dynamic picture storage unit 1285 and the audio storage unit 1206, respectively, and writes the still picture data and a pair of still picture data and audio data of the same time in the storage areas allocated to the time line stream having the identification number in the time line stream storage unit 1288 (Step 1424).

The stream creation unit 1282 writes the start and end times of the inputted dynamic picture display, and the partial image ID of the dynamic picture display object, along with the identification number of the time line stream, in the now working area allocated to the information relating to the dynamic picture display of the page stream in the page stream storage unit 1287 (Step 1425).

In Step 1422, when the audio file does not exist, the stream creation unit 1282 reads the dynamic picture file whose name is inputted from the dynamic storage unit 1283, and writes the contents of the file in the storage areas allocated to the time line stream having the identification number in the time line stream storage unit 1288 (Step 1426), and then starts Step 1421.

Next, the stream creation unit 1282 increments the identification number of the time line stream (Step 1427), and goes back to Step 1419.

In Step 1419, when the dynamic picture display to be described does not exist in the page stream, the stream creation unit 1282 increments the identification number of the page stream (Step 1428), and goes back to Step 1402.

In Step 1442, when the contents to be described do not exist in the page stream, the stream creation unit 1282 requests the input instructing order of recording the page stream and the time line stream successively onto the storage areas of the track of the CD-ROM 1210 (Step 1429). The stream creation unit 1282 posts the recording order to the CD-ROM

22

write unit 1219. The CD-ROM write unit 1219 reads the page stream and the time line stream from the page stream storage unit 1287 and the time line stream storage unit 1288, respectively, and stores them in the CD-ROM 1210 (Step 1430).

As mentioned above, one or a plurality of partial images can be shown by one page stream, and multi-media can be recorded in the CD-ROM 1210; the multi-media information in which parameters for moving, enlarging/reducing, rotating partial images, commands to be executed according to the input signal, and the time line information are described by the page stream. Also, each page stream and time line stream can be stored successively in the storage areas on the same track of the CD-ROM 1210. According to the present embodiment, the multi-media information stored in the multi-media information record device 1290 can be played back from the CD-ROM 1210 effectively by the multi-media information playback device 200.

According to the present embodiment, the still picture data and the audio data shown by the time line stream are compressed and encoded according to the MPEG1, and they are extended and coded by the MPEG1 decoder 311. But, the still picture data, the audio data, and the partial image data can be compressed and encoded by other formats like VFW (Video for Windows) or QT (Quick Time). And the MPEG1 decoder 311 can be substituted for a decoder following other formats. When the multi-media information record device 1290 only deals with data which is not compressed and encoded, there is no problem without a decoder.

(Embodiment 3)

FIG. 16 is a block diagram showing construction of the multi-media information playback device 1600 of the third embodiment of the present invention. FIG. 17 is a block diagram showing hardware construction of the multi-media information playback device shown in FIG. 16.

As shown in FIG. 16, the multi-media information playback device 1600 is connected to a data server 1700 through a network, comprising a network interface unit 1601 and a page load unit 1602. Other elements are the same as the multi-media information playback device 200 shown in FIG. 2, so only the same reference numerals are given without explanation. The multi-media information can be supplied with the CD-ROM 201 and the CD-ROM interface unit 203.

As shown in FIG. 17, the hardware construction of the multi-media information playback device 1600 is the same as that of the multi-media information playback device 200 shown in FIG. 3 except that it comprises a network interface 1701. Explanation of the hardware construction is omitted, since it is the same as that of the multi-media information playback device 200, so only the same reference numerals are given.

The data server 1700 is an external device comprising storage devices like a hardware disc device, which is not illustrated. The data server 1700 stores the page stream shown in FIG. 5 and the time line stream shown in FIG. 6 in the storage device, one page stream being stored as one file and one time line stream as one file. The data server 1700 reads files which contain the corresponding page stream and time line stream from the hard disc device according to the read request from the multi-media information playback device 1600 via the network, and transfers the page stream and the time line stream to the multi-media information playback device 1600.

The network interface unit 1601 is implemented by a network interface 1701. According to the instruction of the page load unit 1602, this unit 1601 reads multi-media

3,767,845

23

information described by the page stream and the time line stream stored in the data server 1700. Specifically, the network interface unit 1601 transmits PT partition showing whether the read request information is the page stream ("P") or the time line stream ("T") as for the page stream or the time line stream designated by the page load unit 1602, along with the identification number and the read request, to the data server 1700 via the network. The network interface unit 1601 receives the page stream or the time line stream transmitted from the data server 1700 according to the read request via the network.

The page load unit 1602 is implemented by the CPU 301. Processing of the page load unit 1602 is the same as that of the page load unit 206 of the first embodiment except that the read request of the page stream and the time line stream are given to the network interface unit 1601 instead of the CD-ROM interface unit 202.

Explanation about the procedure of the playback of the multi-media information playback device 1600 follows next, only focusing the difference between the multi-media information playback devices 1600 and 200.

In Step 701, when the multi-media information playback device 1600 is activated, the page load unit 1602 instructs the network interface unit 1601 to read a predetermined page stream, e.g. the page stream 1 shown in FIG. 8, from the data server 1700. The network interface unit 1601 transfers a PT partition "P", an identification number "1" and its read request to the data server 1700, and receives the page stream "1" from the data server 1700. The page load unit 1602 loads the page stream to the page storage device 210.

The following explanation is about Steps 705-707 when the page stream 1 is loaded.

When the identified input unit is B, the control information execution unit 204 executes a command "Start the clock of the time line," which corresponds to the input signal B. Specifically, the control information execution unit 204 instructs the time line control unit 207 to start the execution of the time line information described by the page stream 1. Next, the time line control unit 207 activates the clock 205 and reads the time line information in the page stream 1. When the designated time line stream exists in the time line information which describes the dynamic picture display, the time line control unit 207 instructs the page load unit 1602 to load the time line stream. In the page stream 1 shown in FIG. 8, an identification number of the time line stream to be displayed in dynamic picture "1" is designated, so the time line control unit 207 instructs the page load unit 1602 to load the time line stream 1 to the page storage unit 210. The page load unit 1602 instructs the network interface unit 1601 to read the time line stream 1, and the network interface unit 1601 transfers a PT partition "T", an identification number "1" and its read request to the data server 1700. The time line stream 1 from the data server 1700 is loaded to the page storage unit 210. The processing afterwards is the same as that of Embodiment 1.

When the identified input signal is C, the control information execution unit 204 executes a command "Read the page stream 2" which corresponds to the input signal C. Specifically, the control information execution unit 204 instructs the page load unit 1602 to load the page stream 2 to the page storage unit 210. The page load unit 1602 instructs the network interface unit 1601 to read the page stream 2. The network interface unit 1601 transfers a PT partition "P", an identification number "2" and its read request to the data server 1700. The page load unit 1602 loads the page stream 2, which is transmitted to the network

24

interface unit 1601 from the data server 1700, to the page storage unit 210. The processing afterwards is the same as that of Embodiment 1.

As mentioned above, the multi-media information playback device 1600 produces the same effect as that of the multi-media information playback device 200 of Embodiment 1 by the page stream and the time line stream from the data server 1700, according to the present embodiment.

The data server 1700 does not necessarily have to store the page stream and the time line stream, separately. The data server 1700 can store them by the identification numbers of each file expressed by ordering numbers and the file. In this case, designation of the page stream and the time line stream described by the page stream information and the time line stream information, and the designation of the page stream and the time line stream by the parameters of the control information execution unit 204 and the time line control unit 207 are carried out by the identification number of each file.

In the present invention, the contents of the time line stream do not necessarily have to be loaded to the page storage unit 210 at a time. For example, the page load unit 206 can load the designated still picture data and the audio data in the designated time line stream to the page storage unit 210 at every display time of the dynamic picture display; the display data creation unit 213 can read the loaded still picture data from the page storage unit 210 and create display data; the time line control unit 207 can transfer the loaded audio data to the audio data storage unit 211. The following processing should be carried out in order to realize the variations mentioned above. The network interface unit 1601 and the data server 1700 reserve the communication areas of the network for a given time corresponding to the dynamic picture display execution time. Then the data server 1700 sends the still picture data and the audio data when they are compressed and encoded according to the MPEG and the like from the file which records time line stream of the read request. The page load unit 1602 loads the still picture image data and the audio data to the page storage unit 210 in the multi-media information playback device 1600 which receives the still picture data and the audio data corresponding to each display time via the network. The loaded still picture data and the audio data are played back at the proper display time by each of the elements of the multi-media information playback device 1600. In the data server 1700, one time line stream is stored in one file. So when the still picture data and the audio data in the same time line stream are read, read request to the data server 1700 does not happen. So, according to the present invention, even though the contents of the time line stream is not loaded to the page storage unit 210 at a time, the still picture data and audio data corresponding to the display time from the same time line stream are read at high speed. So breaks does not happen in the sound and dynamic pictures.

When the dynamic picture display, the time line control unit 207 can directly instruct the network interface unit 1601 to read the designated time line stream.

(Embodiment 4)

FIG. 18 is a block diagram showing the construction of the multi-media information record device 1800 of the fourth embodiment of the present embodiment. FIG. 19 is a block diagram showing hardware construction of the multi-media information record device 1800 shown in FIG. 18.

As shown in FIG. 18, the multi-media information record device 1800 is connected to the data server 1700, instead of the CD-ROM write unit 1200 and the CD-ROM 1210 of the

5,767,845

25

multi-media information record device 1200 shown in FIG. 12, via a communication line, and comprises a data server write unit 1801. Other elements are the same as the multi-media information record device 1200, so explanation is omitted. Only reference numbers are given.

As shown in FIG. 12, the hardware construction of the multi-media information record device 1800 comprises a network interface 1901, instead of the CD-ROM 1309 of the multi-media information record device 1200 shown in FIG. 13. Other elements are the same as the multi-media information record device 1200 shown in FIG. 13. So explanation is omitted. Only reference numbers are given.

The data server 1700 receives the page stream and the time line stream transferred from the data server write unit 1801 along with a write request via a communication line, and stores them in the storage device inside, e.g. a hard disc device which is not illustrated, as individual files.

The data server write unit 1801 is implemented by the network interface 1901. The processing of the data server write unit 1801 is the same as that of the CD-ROM write unit 1309 shown in FIG. 12, but the created page stream and the time line stream are stored in the storage device inside the data server 1700 which is connected via a communication line, instead of the CD-ROM 1310. The data server write unit 1801 reads the time line stream from the time line stream storage unit 1208 according to the notification from the stream creation unit 1203, and transfers a FT partition "T" of the time line stream, an identification number, and the time line stream to the data server 1700 along with the write request. Then the data server 1700 records the page stream in the file having the FT partition "T" and the identification number, and records the time line stream in the file having the FT partition "T" and the identification number.

According to the present embodiment, the multi-media information record device 1800 can store the page stream and the time line stream shown in FIG. 5 and FIG. 6 in the storage device inside the data server 1700 as one file. The present embodiment can produce the same effect mentioned in Embodiment 1 by playing back the page stream and the time line stream recorded by the multi-media information playback device 1600 connected to the data server 1700 via a network. The data server 1700 can store the page stream and the time line stream by the identification numbers of each file, without distinguishing the page stream and the time line stream. In this case, the designation of the page stream and the time line stream described in the information in the page stream and the time line stream, and the designation of the page stream and the time line stream by the parameters of the control information execution unit 204 and the time line control unit 207, are carried out by the identification numbers of each of the files.

Although the present invention has been fully described by way of examples with reference to the accompanying drawings, it is to be noted that various changes and modifications will be apparent to those skilled in the art. Therefore, unless such changes and modifications depart from the scope of the present invention, they should be construed as being included therein.

What is claimed is:

1. A multi-media information playback device which plays back multi-media information recorded in a recording medium comprising:

(a) a disc having pieces of page information successively stored in a storage area, each piece of page information being made up of multi-media information that

26

describes contents of a plurality of screen images, the page information including:

(1) a partial image list having a pair of partial image information showing a partial image of a screen image and display state information showing display state of the partial image; and

(2) control information which describes a command to be executed according to an input signal, including a display state change command instructing to change the display state of the partial image;

(b) a page information read means for reading a piece of page information from the disc;

(c) a display data creation means for creating display data of the screen image by placing the partial image shown by the partial image information on a screen;

(d) a display means for displaying each display data created by the display data creation means;

(e) an input means for receiving an input signal from an operator; and

(f) a command execution means for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information in the page information read by the page information read means, and instructing the display data creation means to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command;

wherein the display data creation means creates new display data according to the command execution means.

2. The multi-media information playback device of claim 1, wherein the page information includes:

(a) the partial image list;

(b) the control information including an animation display command instructing to change and display the display state information of the partial image corresponding to elapsed time; and

(c) time sequence control information including animation control information which describes values of the display state information of the partial image corresponding to the elapsed time;

wherein the command execution means includes:

(a) a first timer for measuring the elapsed time after start of activation; and

(b) an animation display command execution unit for activating the first timer when an input signal corresponding to the animation display command is detected, calculating values of the display state information corresponding to the elapsed time of each of the partial images based on the animation control information at predetermined times, instructing the display data creation means to create new display data by changing the display state of the partial image according to the calculated values of the display state information, and stopping the first timer when execution of the animation display command is completed;

wherein the display data creation means creates new display data according to the animation display command execution unit.

3. The multi-media information playback device of claim 2, wherein the page information includes:

(a) the partial image list having a pair of the partial image information and display state information, the display

5,767,845

27

static information including X-Y coordinates showing a display position of the partial image to be displayed on the screen, X-Y enlargement ratio showing a ratio of size of the partial image shown by the partial image information and a partial image to be displayed on the screen, and a rotational angle between the partial image shown by the partial image information and a partial image to be displayed on the screen; and

(b) time sequence control information including the animation control information which describes at least one among the values of the X-Y coordinates, the X-Y enlargement ratio, and the rotational angle corresponding to the elapsed time;

wherein the animation display command execution unit includes:

(a) an X-Y coordinates calculation unit for calculating the X-Y coordinates corresponding to the elapsed time based on the animation control information at predetermined times;

(b) an X-Y enlargement ratio calculation unit for calculating the X-Y enlargement ratio corresponding to the elapsed time based on the animation control information at predetermined times; and

(c) a rotational angle calculation unit for calculating the rotational angle corresponding to the elapsed time based on the animation control information at predetermined times.

4. The multi-media information playback device of claim 3, wherein there is at least one storage area on the disc for successively storing page information and at least one storage area for successively storing time sequence information, the page information including:

(a) the partial image list,

(b) the control information including a time sequence processing start command instructing to start execution of time sequence processing corresponding to the elapsed time, and

(c) time sequence control information including time sequence processing control information having a name of time sequence information to be played back according to the time sequence processing start command, IDs showing contents of the time sequence information to be played back at predetermined times, and playback state information describing how the time sequence information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list;

wherein the time sequence information has information, which should be played back according to the elapsed time, stored in order of playback;

wherein the command execution means includes:

(a) a second timer for measuring the elapsed time after the start of activation; and

(b) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second timer when playback of the time sequence information is completed;

wherein the multi-media information playback device further includes:

(d) a page storage means, which is implemented by a RAM, for storing the page information read by the page information read means;

28

(b) a time sequence information read means for reading the time sequence information designated by the time sequence processing execution unit from the disc; and

(c) a playback means for playing back the time sequence information read by the time sequence information read means, and instructing the display means to display the time sequence information.

5. The multi-media information playback device of claim 4, wherein the page information includes:

(a) the partial image list,

(b) the control information, and

(c) time sequence control information including time sequence processing control information having a name of first time sequence information as time sequence information to be played back according to the time sequence processing start command, IDs of sound information to be played back at predetermined times, and playback state information which describes how sound information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list;

wherein the time sequence information includes the first time sequence information comprising sound information corresponding to the ID of sound information, the sound information being divided into equal predetermined sizes and placed in order of playback corresponding to the elapsed time;

wherein the time sequence processing execution unit includes a first time sequence processing execution unit for designating the sound information in the first time sequence information corresponding to the elapsed time at predetermined times, when a name of the first time sequence information is shown by the time sequence processing control information;

wherein the playback means includes a sound playback unit for playing back the sound information.

6. The multi-media information playback device of claim 4, wherein the page information includes:

(a) the partial image list,

(b) the control information, and

(c) the time sequence control information including a name of a second time sequence information as time sequence information to be played back according to the time sequence processing start command, pairs of IDs of sound information and image information to be played back at predetermined times, and the playback state information which describes at least one of dynamic picture and animation should be displayed in an area relating to the partial image shown by the partial image information;

wherein the time sequence information includes the second time sequence information comprising sound information divided into equal predetermined sizes and image information showing an image of at least one of the dynamic picture and the animation, the second time sequence information and the image information being placed in order of playback corresponding to the elapsed time;

wherein the time sequence processing execution unit includes a second time sequence processing execution unit for designating sound information and image information in the second time sequence information corresponding to the elapsed time at predetermined times when the second time sequence information is shown by the time sequence processing control information.

5,767,845

29

and instructing the display data creation means to create new display data by placing the partial image read by the time sequence information read means in an area shown by the playback state information;

wherein the display data creation means creates new display data according to the second time sequence processing execution unit.

7. A multi-media information record device for recording multi-media information in a disc, comprising:

(a) a partial image storage means for storing the partial image information of at least one partial image in one partial image file, the partial image information being a part of the screen image;

(b) a partial image list input means for receiving input of a name of at least one partial image file in the partial image storage means and display state information showing display state of the partial image shown by the partial image information in the partial image file;

(c) a page information storage means for having a plurality of separate small storage areas, each of which is used for storing at least a piece of page information which is made up of multi-media information that describes contents of a plurality of screen images;

(d) a partial image list write means for writing a pair of the partial image information and the display state information in a first small storage area in the page information storage means along with the IDs of the partial image information and the display state information, after reading partial image information from the partial image file whose name is inputted, the display state information being inputted according to the partial image information;

(e) a control information input means for receiving input of control information which includes a name of input signal and display state change command instructing to change display state of the partial image corresponding to the input signal;

(f) a control information write means for writing the inputted control information in a second small storage area in the page information storage means; and

(g) a page information record means for successively recording information, which is written as a piece of page information in each small storage area in the page information storage means, in a storage area on the disc.

8. The multi-media information record device of claim 7, wherein the control information includes animation display command instructing to change and display state information of the partial image corresponding to the elapsed time;

wherein the control information input means further includes an animation display command input unit for receiving input of a pair of an input signal and the animation display command;

wherein the multi-media information record device further includes:

(h) a time sequence control information input means for receiving time sequence control information including animation control information, the animation control information describing how display state of the partial image changes according to the elapsed time; and

(i) a time sequence control information write means for writing the inputted time sequence control information in a third small storage area in the page information storage means.

30

9. The multi-media information record device of claim 8, wherein the partial image list input means further includes a display state information input unit for receiving input of display state information for each piece of partial image information, the display information including X-Y coordinates showing a display position of the partial image to be displayed on the screen, X-Y enlargement ratio showing a ratio of size of the partial image shown by the partial image information and a partial image to be displayed on the screen, and a rotational angle between the partial image shown by the partial image information and a partial image to be displayed on the screen;

wherein the time sequence control information input means receives input of animation control information which describes how at least one among the values of the X-Y coordinates, the X-Y enlargement ratio, and the rotational angle changes corresponding to the elapsed time.

10. A multi-media information playback device for reading multi-media information from a data server connected via a network and playing back the multi-media information, comprising:

(a) a page information read means for reading a piece of page information, which is made up of multi-media information that describes contents of a plurality of screen images, stored as one file from a data server connected via a network, the page information including:

(1) a partial image list having at least one pair of the partial image information showing a partial image of a screen image and display state information describing display state of the partial image; and

(2) control information which describes a command to be executed according to an input signal, including a display state change command instructing to change the display state of the partial image;

(b) a display data creation means for creating display data of the screen image by placing the partial image shown by the partial image information on a screen;

(c) a display means for displaying each display data created by the display data creation means;

(d) an input means for receiving an input signal from an operator; and

(e) a command execution means for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information in the page information read by the page information read means, and instructing the display data creation means to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command;

wherein the display data creation means creates new display data according to the command execution means.

11. The multi-media information playback device of claim 10, wherein the page information including:

(a) the partial image list;

(b) the control information including the animation display instructing to change and display state information of the partial image corresponding to the elapsed time; and

(c) time sequence control information including animation control information which describes values of



5,767,845

31

display state information of the partial image corresponding to the elapsed time;

wherein the command execution means includes:

- (a) a first timer for measuring the elapsed time after start of activation; and
- (b) an animation display command execution unit for activating the first timer when an input signal corresponding to the animation display command is detected, calculating values of the display state information corresponding to the elapsed time of each of the partial images based on the animation control information at predetermined times, instructing the display data creation means to create new display data by changing the display state of the partial image according to the calculated values of the display state information, and stopping the first timer when execution of the animation display command is completed;

wherein the display data creation means creates new display data according to the animation display command execution unit.

12. The multi-media information playback device of claim 11, wherein the page information including:

- (a) the partial image list having of at least one pair of the partial image information and the display state information including X-Y coordinates showing a display position of the partial image to be displayed on the screen, X-Y enlargement rates showing a ratio of size of the partial image shown by the partial image information and the partial image to be displayed on the screen, and a rotational angle between the partial image shown by the partial image information and the partial image to be displayed on the screen;
- (b) the control information including the animation display command; and
- (c) time sequence control information including the animation control information which describes at least one among the values of the X-Y coordinates, the X-Y enlargement rates, and the rotational angle corresponding to the elapsed time;

wherein the animation display command execution unit includes:

- (a) an X-Y coordinate calculation unit for calculating the X-Y coordinates corresponding to the elapsed time based on the animation control information at predetermined times;
- (b) an X-Y enlargement rate calculation unit for calculating the X-Y enlargement rates corresponding to the elapsed time based on the animation control information at predetermined times; and
- (c) a rotational angle calculation unit for calculating the rotational angle corresponding to the elapsed time based on the animation control information at predetermined times.

13. The multi-media information playback device of claim 12, wherein the page information including:

- (a) the partial image list;
- (b) the control information including a time sequence processing start command instructing to start execution of time sequence processing corresponding to the elapsed time; and
- (c) time sequence control information including time sequence processing control information having a name of time sequence information to be played back according to the time sequence processing start command, its showing contents of the time sequence

32

information to be played back at predetermined times, and playback state information describing how the time sequence information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list;

wherein the command execution means includes:

- (a) a second timer for measuring the elapsed time after the start of activation; and
- (b) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second timer when playback of the time sequence information is completed;

wherein the multi-media information playback device further includes:

- (a) a page storage means, which is implemented by RAM, for storing the page information read by the page information read means;
- (b) a time sequence information read means for reading contents of the time sequence information designated by the time sequence processing execution unit from the time sequence information stored as one file in the data server via a network; the time sequence information having contents in order of playback corresponding to the elapsed time and its name being included in the time sequence control information; and
- (c) a playback means for playing back the time sequence information ready by the time sequence information read means, and instructing the display means to display the time sequence information.

14. The multi-media information playback device in claim 13, wherein the page information including:

- (a) the partial image list;
- (b) the control information; and
- (c) time sequence control information including time sequence processing control information having a name of the first time sequence information as time sequence information to be played back according to the time sequence processing start command, sound information to be played back according to the elapsed time of the first time sequence information, and playback state information describing how the sound information should be played back in accordance with display of the partial image shown by partial image information in the partial image list;

wherein the time sequence processing execution unit includes a first time sequence processing execution unit for designating the sound information in the first time sequence information corresponding to the elapsed time at predetermined times, when a name of the first time sequence information is shown by the time sequence processing control information;

wherein the time sequence information read means reads the sound information designated by first time sequence processing execution unit from the first time sequence information stored as one file in the data server, the first time sequence information describing the divided sound information in order of playback corresponding to the elapsed time and its name being included in the time sequence control information;

wherein the playback means includes a sound playback unit for playing back the sound information.

5,767,845

33

13. The multi-media information playback device of claim 12, wherein the page information including:

- (a) the partial image file;
- (b) the control information; and
- (c) the time sequence control information including a pair of the second time sequence information as time sequence information to be played back according to the time sequence processing start command, a pair of sound information and image information to be played back corresponding to the elapsed time of the second time sequence information, and playback state information which describes at least one of dynamic picture and animation should be displayed in the area relating to the partial image shown by the partial image information;

wherein the time sequence processing execution unit includes a second time sequence processing execution unit for designating sound information and image information in the second time sequence information corresponding to the elapsed time at predetermined times when the second time sequence information is shown by the time sequence processing control information, and instructing the display data creation means to create new display data by placing the partial image read by the time sequence information read means in an area shown by the playback state information;

wherein the time sequence information read means reads the sound information and the screen image information designated by the second time sequence processing execution unit from the second time sequence information stored as one file in the data server, the time sequence information describing the divided sound information in order of playback and the screen image information describing one screen image of at least one of motion picture and animation corresponding to the elapsed time and its name being included in the time sequence control information;

wherein the display data creation means creates new display data according to the second time sequence processing execution unit.

16. A multi-media information record device for recording multi-media information in a data server connected via a network, comprising:

- (a) a partial image storage means for storing the partial image information of at least one partial image in one partial image file, the partial image information being a part of the screen image;
- (b) a partial image list input means for receiving input of a name of at least one partial image file in the partial image storage means and display state information showing display state of the partial image shown by the partial image information in the partial image file;
- (c) a page information storage means for having a plurality of separate small storage areas, each of which is used for storing at least a piece of page information which is made up of multi-media information that describes contents of a plurality of screen images;
- (d) a partial image list write means for writing a pair of the partial image information and the display state information in a first small storage area in the page information storage means along with the file of the partial image information and the display state information, after reading partial image information from the partial image file whose name is inputted, the display state information being inputted according to the partial image information;

34

(e) a control information input means for receiving input of control information which includes a piece of input signal and display state change command instructing to change display state of the partial image corresponding to the input signal;

(f) a control information write means for writing the inputted control information in a second small storage area in the page information storage means; and

(g) a page information record means for recording contents of a piece of page information in one file in the data server after transvolting contents written as a piece of page information in each storage area in the page information storage means to a data server along with its write request.

17. The multi-media information record device of claim 16, wherein the control information includes animation display command instructing to change and display state information of the partial image corresponding to the elapsed time;

wherein the control information input means further includes an animation display command input unit for receiving input of a pair of an input signal and the animation display command;

wherein the multi-media information record device further includes:

(a) a time sequence control information input means for receiving time sequence control information including animation control information, the animation control information describing how display state of the partial image changes according to the elapsed time; and

(b) a time sequence control information write means for writing the inputted time sequence control information in a third small storage area in the page information storage means.

18. The multi-media information record device of claim 17, wherein the partial image list input means further includes a display state information input unit for receiving input of display state information for each piece of partial image information, the display information including X-Y coordinates showing a display position of the partial image to be displayed on the screen, X-Y enlargement rate showing a ratio of size of the partial image shown by the partial image information and a partial image to be displayed on the screen, and a rotational angle between the partial image shown by the partial image information and a partial image to be displayed on the screen;

wherein the time sequence control information input means receives input of animation control information which describes how at least one among the values of the X-Y coordinates, the X-Y enlargement rate, and the rotational angle change corresponding to the elapsed time.

19. A multi-media information record device for recording multi-media information in a disc, comprising:

(a) a partial image storage means for storing the partial image information of at least one partial image in one partial image file, the partial image information being a part of the screen image;

(b) a partial image list input means for receiving input of a name of at least one partial image file in the partial image storage means and display state information showing display state of the partial image shown by the partial image information in the partial image file;

wherein the partial image list input means further includes a display state information input unit for receiving

5,767,845

35

input of display state information for each piece of partial image information, the display information including X-Y coordinates showing a display position of the partial image to be displayed on the screen, X-Y enlargement rates showing a ratio of size of the partial image shown by the partial image information and a partial image to be displayed on the screen, and a rotational angle between the partial image shown by the partial image information and a partial image to be displayed on the screen;

(c) a page information storage means for having a plurality of separate small storage areas, each of which is used for storing at least a piece of page information;

(d) a partial image list write means for writing a pair of the partial image information and the display state information in a first small storage area in the page information storage means along with the IDs of the partial image information and the display state information, after reading partial image information from the partial image file whose name is inputted, the display state information being inputted according to the partial image information;

(e) a control information input means for receiving input of control information which includes a pair of input signal and display state change command instructing to change display state of the partial image corresponding to the input signal;

wherein the control information includes animation display command instructing to change and display state information of the partial image corresponding to the elapsed time;

wherein the control information input means further includes an animation display command input unit for receiving input of a pair of an input signal and the animation display command;

(f) a control information write means for writing the inputted control information in a second small storage area in the page information storage means;

(g) a page information record means for successively recording information, which is written as a piece of page information in each small storage area in the page information storage means, in a storage area on the disc;

(h) a time sequence control information input means for receiving time sequence control information including animation control information, the animation control information describing how display state of the partial image changes according to the elapsed time;

wherein the time sequence control information input means receives input of animation control information which describes how at least one among the values of the X-Y coordinates, the X-Y enlargement rates, and the rotational angle changes corresponding to the elapsed time;

(i) a time sequence control information write means for writing the inputted time sequence control information in a third small storage area in the page information storage means;

(j) a time sequence information storage means having a piece of time sequence information stored in each time sequence information file, the time sequence information having information written in order of playback corresponding to the elapsed time; and

(k) a time sequence information record means for successively recording time sequence information in a

36

storage area on the disc after receiving input of a name of at least one time sequence information file in the time sequence information storage means, reading time sequence information from the time sequence information file whose name is inputted, and correlating the time sequence information with a name of time sequence information corresponding to the name of the file;

wherein the control information input means further includes a time sequence processing start command input unit for receiving input of a pair of an input signal and a time sequence processing start command in the control information, the time sequence processing start command instructing to start execution of time sequence processing corresponding to the elapsed time and being included in the control information;

wherein the time sequence control information input means further includes a time sequence processing control information input unit for receiving input of the time sequence processing control information which includes a name of time sequence information to be played back according to the time sequence processing start command, its showing context of the time sequence information to be played back at predetermined times, and playback state information which describes how the time sequence information should be played back in accordance with display of the partial image list, the time sequence processing control information being included in the time sequence control information.

20. The multi-media information record device of claim 19, wherein the time sequence information includes first time sequence information in which sound information is divided into predetermined equal data data, the sound information being written along with its ID in order of playback corresponding to the elapsed time;

wherein the time sequence information record means includes a first time sequence information record unit for recording first time sequence information in the disc after reading the first time sequence information from the time sequence information file, whose name is inputted, when a name of the first time sequence information is inputted; and

wherein the time sequence processing control information input unit includes first time sequence processing control information input unit for receiving input of first time sequence processing control information which includes a name of first time sequence information to be played back according to time sequence processing start command of the page information, its of sound information to be played back at predetermined times, and playback state information which describes how the sound information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list, the first time sequence control information being included in the time sequence processing control information.

21. The multi-media information record device of claim 19, wherein the time sequence information record means includes a second time sequence information record unit for recording second time sequence information in the disc after reading the second time sequence information from the time sequence information file, whose name is inputted, when a name of the second time sequence information is inputted, the second time sequence information having sound information divided into predetermined equal data data, image information showing one screen image of at least one of

5,767,845

37

animation and dynamic picture and its of the sound information and the image information written in order of playback corresponding to the elapsed time; and

wherein the time sequence processing control information input unit includes a second time sequence processing control information input unit for receiving input of second time sequence processing control information which includes a name of second time sequence information to be played back according to time sequence processing start command of the page information, pairs of its of sound information and image information to be played back at predetermined times, and the playback state information describing at least one of dynamic picture and animation should be displayed in an area relating to partial image shown by the partial image information in the partial image file.

22. A multi-media information record device for recording multi-media information in a data server connected via a network, comprising:

(a) a partial image storage means for storing the partial image information of at least one partial image in one partial image file, the partial image information being a part of the screen image;

(b) a partial image list input means for receiving input of a name of at least one partial image file in the partial image storage means and display state information showing display state of the partial image shown by the partial image information in the partial image file;

(c) a page information storage means for having a plurality of separate small storage areas, each of which is used for storing at least a piece of page information which is made up of multi-media information that describes contents of a plurality of screen images;

(d) a partial image list write means for writing a pair of the partial image information and the display state information in a first small storage area in the page information storage means along with the IDs of the partial image information and the display state information, after reading partial image information from the partial image file whose name is inputted, the display state information being inputted according to the partial image information;

wherein the partial image list input means further includes a display state information input unit for receiving input of display state information for each piece of partial image information, the display information including X-Y coordinates showing a display position of the partial image to be displayed on the screen, X-Y enlargement rates showing a ratio of size of the partial image shown by the partial image information and a partial image to be displayed on the screen, and a rotational angle between the partial image shown by the partial image information and a partial image to be displayed on the screen;

(e) a control information input means for receiving input of control information which includes a name of input signal and display state change command instructing to change display state of the partial image corresponding to the input signal;

wherein the control information includes animation display command instructing to change and display state information of the partial image corresponding to the elapsed time;

wherein the control information input means further includes an animation display command input unit for receiving input of a pair of an input signal and the animation display command;

38

(f) a control information write means for writing the inputted control information in a second small storage area in the page information storage means;

(g) a page information record means for recording contents of a piece of page information in one file in the data server after transmitting contents which is a piece of page information in each storage area in the page information storage means to a data server along with its write request;

(h) a time sequence control information input means for receiving time sequence control information including animation control information, the animation control information describing how display state of the partial image changes according to the elapsed time;

wherein the time sequence control information input means receives input of animation control information which describes how at least one among the values of the X-Y coordinates, the X-Y enlargement rates, and the rotational angle changes corresponding to the elapsed time;

(i) a time sequence control information write means for writing the inputted time sequence control information in a third small storage area in the page information storage means;

(j) a time sequence information storage means having a piece of time sequence information stored in each time sequence information file, the time sequence information having information written in order of playback corresponding to the elapsed time; and

(k) a time sequence information record means for recording contents of time sequence information in one file in the data server for each piece of time sequence information, after receiving a name of at least one time sequence information file in the time sequence information storage means, reading time sequence information from the time sequence information file whose name is inputted, correlating the time sequence information with a name of time sequence information corresponding to the file, and transmitting the time sequence information to the data server along with its write request;

wherein the control information input means further includes a time sequence processing start command input unit for receiving input of a pair of an input signal and a time sequence processing start command in the control information, the time sequence processing start command instructing to start execution of time sequence processing corresponding to the elapsed time and being included in the control information, wherein the time sequence control information input means further includes a time sequence processing control information input unit for receiving input of the time sequence processing control information which includes a name of time sequence information to be played back according to the time sequence processing start command, IDs showing contents of the time sequence information to be played back at predetermined times, and playback state information which describes how the time sequence information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list, the time sequence processing control information being included in the time sequence control information.

23. The multi-media information record device of claim 22, wherein the time sequence information includes first

5,767,845

39

time sequence information in which sound information is divided into predetermined equal data sizes, the sound information being written along with its ID in order of playback corresponding to the elapsed time, wherein the time sequence information record means includes a first time sequence information record unit for recording first time sequence information in the disc after reading the first time sequence information from the time sequence information file, whose name is inputted, when a name of the first time sequence information is inputted; wherein the time sequence processing control information input unit includes first time sequence processing control information input unit for receiving input of first time sequence processing control information which includes a name of first time sequence information to be played back according to time sequence processing start command of the page information, IDs of sound information to be played back at predetermined times, and playback state information which describes how the sound information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list, the first time sequence control information being included in the time sequence processing control information.

24. The multi-media information record device of claim 22, wherein the time sequence information record means includes a second time sequence information record unit for recording second time sequence information in the disc after reading the second time sequence information from the time sequence information file, whose name is inputted, when a name of the second time sequence information is inputted, the second time sequence information having sound information divided into predetermined equal data sizes, image information showing one screen image of at least one of animation and dynamic picture and IDs of the sound information and the image information written in order of playback corresponding to the elapsed time;

wherein the time sequence processing control information input unit includes a second time sequence processing control information input unit for receiving input of second time sequence processing control information which includes a name of second time sequence information to be played back according to time sequence processing start command of the page information, pairs of IDs of sound information and image information to be played back at predetermined times, and the playback state information describing at least one of dynamic picture and animation should be displayed in an area relating to partial image shown by the partial image information in the partial image list.

25. A multi-media information playback device which plays back multi-media information recorded in a recording medium comprising:

(a) a disc having pieces of page information successively stored in a storage area, each piece of page information being made up of multi-media information that describes contents of a plurality of screen images, the page information including:

(1) a partial image list having a pair of partial image information showing a partial image of a screen image and display state information showing display state of the partial image;

(2) control information which describes a command to be executed according to an input signal, the control information including:

a display state change command instructing to change the display state of the partial image; an animation display command instructing to change and display the display state information of the partial image corresponding to elapsed time; and

40

a time sequence processing start command instructing to start execution of time sequence processing corresponding to the elapsed time;

(3) time sequence control information having information, which should be played back according to the elapsed time, stored in order of playback, the time sequence control information including:

(a) animation control information which describes values of the display state information of the partial image corresponding to the elapsed time; and

(b) time sequence processing control information having a name of time sequence information to be played back according to the time sequence processing start command, IDs showing contents of the time sequence information to be played back at predetermined times, and playback state information describing how the time sequence information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list;

(b) a page information read means for reading a piece of page information from the disc;

(c) a display data creation means for creating display data of the screen image by placing the partial image shown by the partial image information on a screen;

(d) a display means for displaying each display data created by the display data creation means;

(e) an input means for receiving an input signal from an operator; and

(f) a command execution means for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information in the page information read by the page information read means, and instructing the display data creation means to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command; the command execution means including:

(1) a first timer for measuring the elapsed time after start of activation;

(2) an animation display command execution unit for activating the first timer when an input signal corresponding to the animation display command is detected, calculating values of the display state information corresponding to the elapsed time of each of the partial images based on the animation control information at predetermined times, instructing the display data creation means to create new display data by changing the display state of the partial image according to the calculated values of the display state information, and stopping the first timer when execution of the animation display command is completed;

(3) a second timer for measuring the elapsed time after the start of activation; and

(4) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second timer when playback of the time sequence information is completed;

5,767.845

41

wherein the display data creation means creates new display data according to the animation display command execution unit;

(g) a page storage means, which is implemented by RAM, for storing the page information read by the page information read means;

(h) a time sequence information read means for reading the time sequence information designated by the time sequence processing execution unit from the disk; and

(i) a playback means for playing back the time sequence information read by the time sequence information read means, and instructing the display means to display the time sequence information.

26. A multi-media information playback device which plays back multi-media information recorded in a recording medium comprising:

(a) a disc having pieces of page information successively stored as one file from a data server connected via a network, each piece of page information being made up of multi-media information that describes contents of a plurality of screen images, the page information including:

(1) a partial image list having a pair of partial image information showing a partial image of a screen image and display state information showing display state of the partial image;

(2) control information which describes a command to be executed according to an input signal, the control information including:

a display state change command instructing to change the display state of the partial image;  
an animation display command instructing to change and display the display state information of the partial image corresponding to elapsed time; and  
a time sequence processing start command instructing to start execution of time sequence processing corresponding to the elapsed time;

(3) time sequence control information having information, which should be played back according to the elapsed time, stored in order of playback, the time sequence control information including:

(a) animation control information which describes values of the display state information of the partial image corresponding to the elapsed time; and

(b) time sequence processing control information having a name of time sequence information to be played back according to the time sequence processing start command, its showing contents of the time sequence information to be played back at predetermined time, and playback state information describing how the time sequence information should be played back in accordance with display of the partial image shown by the partial image information in the partial image list;

(b) a page information read means for reading a piece of page information from the disc;

(c) a display data creation means for creating display data of the screen image by placing the partial image shown by the partial image information on a screen;

42

(d) a display means for displaying each display data created by the display data creation means;

(e) an input means for receiving an input signal from an operator; and

(f) a command execution means for detecting the input signal inputted by the operator, judging whether the input signal corresponds to the command described by the control information, the page information read by the page information read means, and instructing the display data creation means to create new display data by changing the display state of the corresponding partial image according to the display state change command when the input signal corresponds to the display state change command; the command execution means including:

(1) a first timer for measuring the elapsed time after start of activation;

(2) an animation display command execution unit for activating the first timer when an input signal corresponding to the animation display command is detected, calculating values of the display state information corresponding to the elapsed time of each of the partial images based on the animation control information at predetermined times, instructing the display data creation means to create new display data by changing the display state of the partial image according to the calculated values of the display state information, and stopping the first timer when execution of the animation display command is completed;

(3) a second timer for measuring the elapsed time after the start of activation; and

(4) a time sequence processing execution unit for activating the second timer when an input signal corresponding to the time sequence processing start command is detected, designating contents of the time sequence information corresponding to the elapsed time, and stopping the second timer when playback of the time sequence information is completed;

wherein the display data creation means creates new display data according to the animation display command execution unit;

(g) a page storage means, which is implemented by RAM, for storing the page information read by the page information read means;

(h) a time sequence information read means for reading the time sequence information designated by the time sequence processing execution unit from the time sequence information stored as one file in the data server via a network, the time sequence information having contents in order of playback corresponding to the elapsed time and its name being included in the time sequence control information; and

(i) a playback means for playing back the time sequence information read by the time sequence information read means, and instructing the display means to display the time sequence information.

\* \* \* \* \*

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**